

***Interactive comment on* “Technical Note: Cost-efficient approaches to measure carbon dioxide (CO₂) fluxes and concentrations in terrestrial and aquatic environments using mini loggers” by D. Bastviken et al.**

Anonymous Referee #1

Received and published: 10 February 2015

GENERAL COMMENTS

The authors report three designs of chambers equipped with an inexpensive commercial CO₂ analyzer for measurements of soil-air fluxes, water-air fluxes and water pCO₂. The method to derive water pCO₂ is new and unorthodox. In my opinion, this method still requires to be more thoroughly tested against more traditional methods.

I will not provide specific comments on the experimental setup for air-soil fluxes since this is not within my field of expertise and I have actually never done this sort of measurements. From conversations with colleagues that do those measurements, I was

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



told that the method is very sensitive to variations within the chamber of barometric pressure, with over-pressure suppressing the CO₂ efflux and under-pressure artificially enhancing the CO₂ efflux. Apparently, this is a bigger issue than for chamber measurements of air-water fluxes. I suggest that authors look this up in literature.

MAJOR COMMENTS

One concern that might not need to be settled in this paper, but might be a more general discussion for the whole carbon community working on inland waters is whether we can trust chamber measurements to derive more or less correct air-water CO₂ fluxes. The authors provide an instrumental design that could allow deriving with reasonable funding a huge data-set of air-water CO₂ fluxes from inland waters with fully-automated chambers. But as a community do we want to generate a huge flow of potentially erroneous data (with chambers) or should we prefer to have more restricted data-sets of potentially better quality (based on computed *k* values and pCO₂ measurements or based on more expensive but probably more rigorous eddy covariance flux measurements)? Personally, I would prefer to see an increase of high quality direct pCO₂ measurements (refer to Abril et al. 2015) rather than flux measurements with chambers (or with eddy covariance for that matter). As a biogeochemist, I have a better grasp on pCO₂ as a quantity for understanding drivers and dynamics rather than CO₂ fluxes that are overwhelmingly driven by the gas transfer velocity that is a function of a myriad of physical processes.

Another concern is that it would have been useful and extremely informative if the method to measure water pCO₂ could have been checked against traditional methods. The authors checked the actual CO₂ sensor against a LGR instrument and GC which is useful, but there is no quality check on the actual water pCO₂ measurements obtained on the lake and river.

A final major comment would be that the design the authors propose does not cover the full spectrum of approaches (= data) needed to better constrain CO₂ fluxes from inland

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper

waters. If we assume that on deployment the $p\text{CO}_2$ is at atmospheric value and that the water $p\text{CO}_2$ is 6000 ppm, for a medium sized lake under average wind speeds I would expect equilibrium in the chamber to take several hours, maybe half a day (the authors should actually compute this, see hereafter). This is clearly not suited if you want to describe the spatial variability of $p\text{CO}_2$ in a large river network in a remote place of the planet during a field expedition that by nature is limited in time (by manpower and financial constrains). In this case, you'll want a fast discrete sample (about 15 min) for instance based on syringe headspace equilibration (e.g. Abril et al. 2015) to do as many samples as logistically possible; alternatively if you can sail the river network with a boat, you'll want a flow-through equilibrator system for continuous measurements in surface waters (e.g. Abril et al. 2014). However, these two techniques could also be easily been implemented with SenseAir instruments, obviously using a different design than the one proposed here.

SPECIFIC COMMENTS

P 2359 L3-7: It might be worth mentioning that air-water gas flux measurements with chamber measurements have been heavily criticized in the past (Liss and Merlivat 1986; Belanger and Korzum 1991; Raymond and Cole 2001; Matthews et al. 2003), and this debate remains largely unresolved, although there are some interesting comparisons between chambers and other techniques (Guérin et al. 2007; Gålfalk et al. 2013; Huotari et al. 2013).

P2359 L 16 : $p\text{CO}_2$ on itself is a useful and interesting variable for biogeochemical studies, it is not solely used for calculating fluxes.

P2359 L 25 : Equation (1) has been around before the Cole and Caraco (98) paper, please refer to Liss and Slater (1974).

P2359 L 28 : papers by Raymond et al. (2012) and Abril et al. (2009) might be useful here.

[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)[Discussion Paper](#)

P2360 L10-13 : I suggest to mention that there are more straightforward and updated methods to measure pCO₂ such as flow-through equilibrators (some that can be very compact such a membrane contractors) coupled to infra-red analyzers for direct real-time measurements, or syringe equilibration and injection into an infra-red analyzer deployed in the field for near-real time measurements. These systems can be designed to be compact and portable, and have been used in a variety of inland waters including very remote places (e.g. Abril et al. 2015). Also, fully automated systems that can run autonomously on buoys during long deployments are routinely used by the ocean community (Sutton et al. 2014), and such systems can be deployed on lakes and even large rivers. Finally, Hari et al. (2008) proposed a system based on small Vaisala CO₂ sensors that was according to the authors was compact and could be deployed moored for a few days, although I have not seen further studies using such a system.

P 2360 L 24 : SAMI is sold as a CO₂ sensor when in fact it makes a sophisticated pH measurement from which pCO₂ is computed. Direct CO₂ sensors based on membrane equilibration coupled to infra-red detection commercially available include ProOceanus and Contros.

There's a redundancy between statements in P 2361 L 8-10 and in P 2361 L17-18.

P 2361 L 13 : PP systems and Vaisala also produce infra-red analyzers that are commonly used in CO₂ research.

P 2361 L 20 : it could be useful to provide a table with the relevant characteristics (given by manufacturer) of the different available instruments (size, weight, power requirement, measurement range, accuracy, resolution, stability), and relative price normalized to the price of the Senseair (ratio of prices).

P2362 L 19 : provide accurate power requirement in Watts or Amps@12VDC

P2362 L 22 : specify what is meant by “convenient calibration” ?

P 2365 L 3 : paper by Zhao et al. (2015) might be useful here.

[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)[Discussion Paper](#)

P 2367 L 2 : it should be easy to compute based on the volume of the chamber a range of equilibration times, based on a realistic range of K values and a range of final pCO₂ values (assuming the initial pCO₂ = atmospheric) to attain for instance 95% of full equilibrium. This could be useful to better grasp the limitations of the proposed method.

P 2368 L 8: Or alternatively to recalibrate regularly the instrument.

P 2368 L 17-18: The calculation of the flux is based on the slope of pCO₂ change during the chamber deployment (30 min). It's a relative change, so even if the instrument drifts and the absolute pCO₂ values are off, the slope (hence the flux) will still be correct (or applicable for the purpose of computing the flux).

P 2368 L 26 : I'm not sure what's the point of comparing the fluxes in a Nordic lake with data obtained in India. This does not provide any sort of validation of the technique. The fluxes could be over-estimated by 50% due to a major flaw in the experimental design, the values would still fall within the range of values of CO₂ fluxes in lakes globally reported in previously published papers.

P 2371 L3-5 : Based on the volume of water and headspace, Henry law's constant, and basic considerations on mass conservation and partitioning of gas between water and gaseous phases it is possible to compute accurately the original dissolved CO₂ concentration.

P 2371 L 20 : Abril et al. (2015) demonstrated very convincingly that indirect measurements are highly biased rather than just " suggested " as stated in this sentence.

REFERENCES

Abril G., S. Bouillon, F. Darchambeau, C. R. Teodoru, T. R. Marwick, F. Tamooh, F. O. Omengo, N. Geeraert, L. Deirmendjian, P. Polsenaeere & A.V. Borges (2015) Technical Note: Large overestimation of pCO₂ calculated from pH and alkalinity in acidic, organic-rich freshwaters, Biogeosciences, 12(1):67-78

[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)[Discussion Paper](#)

Abril, G., Martinez, J.-M., Artigas, L.F., Moreira-Turcq, P., Benedetti, M.F., Vidal L., Meziane, T., Kim, J.-H., Bernardes, M.C., Savoye, N., Deborde, J., Albéric, P., Souza, M.F.L., Souza, E.L. and Roland, F. (2014) Amazon River Carbon Dioxide Outgassing fuelled by Wetlands, *Nature* 505, 395–398.

Abril G., Commarieu M.V., Sottolichio A., Bretel P. and Guérin F. (2009) Turbidity limits gas exchange in a large macrotidal estuary. *Estuarine Coastal and Shelf Science*. 83: 342–348.

Belanger T. V. and Korzum E. A. (1991) Critique of floating-dome technique for estimating reaeration rates. *Journal of Environmental Engineering* 117:144-150.

Gålfalk, M., D. Bastviken, S. Fredriksson, and L. Arneborg (2013), Determination of the piston velocity for water-air interfaces using flux chambers, acoustic Doppler velocimetry, and IR imaging of the water surface, *J. Geophys. Res. Biogeosci.*, 118, 770–782, doi:10.1002/jgrg.20064

Guérin, F., G. Abril, D. Serça, C. Delon, S. Richard, R. Delmas, A. Tremblay, and L. Varfalvy (2007), Gas transfer velocities of CO₂ and CH₄ in a tropical reservoir and its river downstream, *J. Mar. Syst.*, 66, 161– 172.

Hari et al. (2008) High-frequency measurements of productivity of planktonic algae using rugged nondispersive infrared carbon dioxide probes, *Limnol. Oceanogr.: Methods* 6, 347–354

Huotari, J., S. Haapanala, J. Pumpanen, T. Vesala, and A. Ojala (2013), Efficient gas exchange between a boreal river and the atmosphere, *Geophys. Res. Lett.*, 40, 5683–5686, doi:10.1002/2013GL057705.

Liss P. S. and Merlivat L. (1986) Air-sea exchange rates: introduction and synthesis. In *The role of air-sea exchanges in geochemical cycling* ed. P. Buat-Ménard, pp. 113-127, Reidel, Dordrecht.

Liss, P. S., and Slater P. G (1974) Flux of gases across the air-sea interface. *Nature*,

[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)[Discussion Paper](#)

233:327-9.

Matthews C. J. D., St. Louis V. L. and Hesslein R. H. (2003) Comparison of three techniques used to measure diffusive gas exchange from sheltered aquatic surfaces. *Environmental Science and Technology* 37:772-780.

Raymond et al. (2012) Scaling the gas transfer velocity and hydraulic geometry in streams and small rivers, *Limnology and Oceanography: Fluids and Environments* 2: 41-53.

Raymond P. A. and Cole J. J. (2001) Gas exchange in rivers and estuaries: Choosing a gas transfer velocity. *Estuaries* 24:312-317.

Sutton et al. (2014) A high-frequency atmospheric and seawater pCO₂ data set from 14 open ocean sites using a moored autonomous system, *Earth Syst. Sci. Data*, 6, 353–366.

Zhao et al. (2015) A comparison of methods for the measurement of CO₂ and CH₄ emissions from surface water reservoirs: Results from an international workshop held at Three Gorges Dam, June 2012, *Limnol. Oceanogr.: Methods* 13, 2015, 15–29.

[Interactive comment on Biogeosciences Discuss., 12, 2357, 2015.](#)

BGD

12, C120–C126, 2015

[Interactive
Comment](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)

[Discussion Paper](#)