

Uncertainties, sensitivities and robustness of simulated water erosion in an EPIC-based global-gridded crop model

Tony W. Carr^{1,*}, Juraj Balkovič^{2,3}, Paul E. Dodds¹, Christian Folberth², Emil Fulajtar⁴, Rastislav Skalsky^{2,5}

¹University College London, Institute for Sustainable Resources, London, United Kingdom

²International Institute for Applied Systems Analysis, Ecosystem Services and Management Program, Laxenburg, Austria

³Department of Soil Science, Faculty of Natural Sciences, Comenius University in Bratislava, Bratislava, Slovak Republic

⁴International Atomic Energy Agency, Joint FAO/IAEA Division of Nuclear Techniques in Food and Agriculture, Vienna, Austria

⁵National Agricultural and Food Centre, Soil Science and Conservation Research Institute, Bratislava, Slovak Republic

* Correspondence to: Tony Carr (tony.carr.16@ucl.ac.uk)

Abstract. Water erosion on arable land can reduce soil fertility and agricultural productivity. Despite the impact of water erosion on crops, it is typically neglected in global crop yield projections. Furthermore, previous efforts to quantify global water erosion have paid little attention to the effects of field management on the magnitude of water erosion. In this study, we analyse the robustness of simulated water erosion estimates in maize and wheat fields between the years 1980 to 2010 based on daily model outputs from a global gridded version of the Environmental Policy Integrated Climate (EPIC) crop model. Using the MUSS water erosion equation and country-specific and environmental indicators determining different intensities in tillage, residue handling and cover crops, we obtained the global median water erosion rates of $7 \text{ t ha}^{-1} \text{ a}^{-1}$ in maize fields and $5 \text{ t ha}^{-1} \text{ a}^{-1}$ in wheat fields. A comparison of our simulation results with field data demonstrates an overlap of simulated and measured water erosion values for the majority of global cropland. Slope inclination and daily precipitation are key factors in determining the agreement between simulated and measured erosion values and are the most critical input parameters controlling all water erosion equations included in EPIC. The many differences between field management methods worldwide, the varying water erosion estimates from different equations and the complex distribution of cropland in mountainous regions add uncertainty to the simulation results. To reduce the uncertainties in global water erosion estimates, it is necessary to gather more data on global farming techniques, to reduce the uncertainty in global land use maps and to collect more data on soil erosion rates representing the diversity of environmental conditions where crops are grown.

1 Introduction

Water erosion is widely recognized as a threat to global agriculture (den Biggelaar et al., 2004; Kaiser, 2004; Panagos et al., 2018; Pimentel, 2006). The removal of topsoil by surface runoff reduces soil fertility and crop

39 yields due to loss of nutrients, degradation of the soil structure, and decreasing plant-available water capacity
40 (Våje et al., 2005). Water erosion is a natural process, but the impact of agricultural field management on surface
41 cover and roughness is decisive for the magnitude of water erosion. High energy precipitation, steep slopes and
42 lack of vegetation cover intensify water erosion. The most vulnerable areas are mountainous regions, due to steep
43 slopes, the tropics and subtropics, due to abundant high energy precipitation, and arid regions, where precipitation
44 events are rare but often intense and the vegetation cover is sparse. This global distribution of water erosion is
45 indicated by suspended sediment in rivers (Walling and Webb, 1996). South America, Sub-Saharan Africa, South
46 and East Asia have been identified as the most vulnerable regions to erosion on agricultural land by several prior
47 studies (Borrelli et al., 2017; Pimentel et al., 1995).

48 Despite its importance for global agriculture, water erosion is usually not considered in global gridded crop model
49 (GGCM) studies. Throughout the past decade, GGCMs - typically combinations of agronomic or ecosystem
50 models and global gridded input data infrastructures - have become essential tools for climate change impact
51 assessments, evaluations of agricultural externalities, and as input data providers for agro-economic models
52 (Mueller et al., 2017). Few assessments have considered land degradation processes and found their inclusion and
53 understanding crucial for evaluating climate change mitigation and adaptation strategies (Balkovič et al., 2018;
54 Chappell et al., 2016). Beyond crop models, there is a need to improve the representation of agricultural
55 management and soil-related processes in earth system models to better reflect carbon sinks and sources (Luo et
56 al., 2016; McDermid et al., 2017; Pongratz et al., 2018). Moreover, improving the representation of water erosion
57 in large-scale models is urgently needed to inform major environmental and agricultural policy programs such as
58 the European Union's Common Agricultural Policy (CAP), the United Nations Sustainable Development Goals
59 (SDGs), the United Nations Convention to Combat Desertification (UNCCD) and the Intergovernmental Science-
60 Policy Platform on Biodiversity and Ecosystem Services (IPBES) (Alewell et al., 2019). Yet, the necessary
61 algorithms to simulate water erosion are often not incorporated in such models. Exceptions among field-scale crop
62 models, which are frequently used in GGCM ensemble studies, are the Environmental Policy Integrated Climate
63 model (EPIC) and Agricultural Production Systems Simulator (APSIM). Compared to other commonly used crop
64 models in GGCMs, EPIC stands out in its detailed representation of soil processes including water erosion and
65 the impacts of tillage on soil properties (Folberth et al., 2019).

66 Recently, water erosion models such as the Universal Soil Loss Equation (USLE) and the Revised Universal Soil
67 Loss Equation (RUSLE) have been used to estimate global water erosion. Annual global soil removal estimates
68 and water erosion rates on cropland of recent studies range between 13 – 22 Gt and 11 - 13 t ha⁻¹ (Borrelli et al.,
69 2017; Doetterl et al., 2012; van Oost et al., 2007). USLE and its modifications were developed in the Midwestern
70 United States and should ideally be evaluated against soil erosion measurements when used for other agro-
71 environmental zones (Evans and Boardman, 2016). However, the uneven distribution of field data around the
72 world, the lack of long-term soil measurements in most global regions, and the great variability of the designs of
73 erosion rate measurements hamper the evaluation of global soil loss estimates derived from models (Auerswald
74 et al., 2004; Borrelli et al., 2017; García-Ruiz et al., 2015). In addition, model input data on topography, soil
75 properties and land use are often aggregated over large areas and thus simulation results cannot be directly
76 compared to single field measurements at specific locations.

77 Most global soil removal estimates using water erosion models are based on static observation approaches or on
78 very coarse timescales that do not fall below annual time steps (Borrelli et al., 2017). Therefore, seasonal patterns
79 of soil cover and precipitation intensities are neglected even though they are crucial factors for water erosion. The
80 state of the soil and its cover is influenced by land management, such as the choice of crops, planting and harvest
81 dates, tillage and plant residue management. Accordingly, neglecting the impact of seasonal changes in vegetation
82 cover and field management practices constitutes large uncertainty in global water erosion estimates. Crop models
83 usually simulate crop growth on a daily timescale, which allows attached water erosion models to account for
84 daily changes in weather, soil properties and vegetation cover. However, uncertainty remains due to the increasing
85 requirement of input data for daily simulations, which is especially challenging at a global scale.

86 The overall aim of this study is (i) to analyse the robustness of water erosion estimates in all global agro-
87 environmental regions simulated with an EPIC-based global-gridded crop model and (ii) to discuss the main
88 drivers affecting the robustness and the uncertainty of simulated water erosion rates on a global scale. We simulate
89 global water erosion rates in maize and wheat fields using different empirical erosion equations in EPIC while
90 accounting for the daily crop growth and development under different field management scenarios. Here, maize
91 and wheat are used as representative crops of global agriculture, as they are grown under most environmental
92 conditions and represent contrasting soil cover patterns. Our global simulations are carried out for a baseline crop
93 management scenario based on a set of environmental and country-specific assumptions and indicators, which is
94 a common practice in global gridded crop modelling. In addition, we quantify the uncertainties of simulated water
95 erosion values stemming from (i) uncertain field management inputs, and (ii) water erosion calculation methods.
96 We also evaluate the model's sensitivity to all inputs involved in the water erosion calculation to interpret the
97 variability and uncertainties of the simulation results, and to discuss the differences between water erosion
98 equations. Finally, we use field measurements from various locations world-wide to evaluate the robustness of
99 estimated water erosion rates under different environmental conditions.

100 **2 Methods**

101 The simplified framework in Figure 1 illustrates the particular stages of the methodological procedure applied by
102 this study and their relationships to input data and model outputs. Both, input and output data are used twofold.
103 We use input data (i) to simulate daily maize and wheat growth and water erosion with EPIC, and (ii) to analyse
104 the sensitivity of relevant model parameters to simulate global water erosion with all equations in EPIC. We use
105 model outputs (i) to calculate a baseline global water erosion scenario, and (ii) to address the uncertainty of
106 simulation results. The final step of this study consists of the robustness check of the model outputs using field
107 data. A detailed description of each element of this study is described in the following sections.

108

109 **2.1 Modelling water erosion and crop growth with EPIC**

110 **2.1.1 Global gridded crop model and input data**

111 We use a global gridded version of the Environmental Policy Integrated Climate (EPIC) crop model, EPIC-IIASA
112 (Balkovič et al., 2014), to simulate soil sediment loss with runoff from 1980 to 2010 while accounting for the
113 daily growth of maize and wheat under different field management scenarios. EPIC can simulate the growth of a
114 wide range of crops and has a sophisticated representation of carbon, nutrient and water dynamics as well as a

115 wide variety of possible field management options, including tillage operations and crop rotations (Izaurre et al., 2006; Sharpley and Williams, 1990). Originally EPIC was named Erosion-Productivity Impact Calculator and 116 was developed to determine the relationship between erosion and soil productivity. Due to its origin, EPIC has 117 several options to calculate water erosion caused by precipitation, runoff and irrigation (Williams, 1990). 118

119 EPIC-IIASA requires global soil and topography data and daily weather data. The basic spatial resolution of the 120 model is 5' x 5' at which soil and topographic data are provided. These are aggregated to homogenous response 121 units and further intersected with a 30' x 30' climate grid, the resolution at which global gridded climate data are 122 available. This results in a total of 131,326 grid cells with a spatial resolution ranging between 5' to 30' (about 9 123 km to 56 km near the equator) (Skalský et al., 2008). We use global daily weather data from the AgMERRA 124 dataset for the years 1980-2010 (Ruane et al., 2015), soil information from the Harmonized World Soil Database 125 (FAO/IIASA/ISRIC/ISSCAS/JRC, 2009), and topography from USGS GTOPO30 (USGS, 1997). Each grid cell 126 is represented by a single field characterized by the combination of topography and soil conditions prevailing in 127 this landscape unit. Each representative field has a defined slope length (20 – 200 m) and field size (1 - 10 ha) 128 based on a set of rules for different slope classes (Table S1). The slope of each representative field is determined 129 by the slope class covering the largest area in each grid cell (Table S1). Slope classes are taken from a global 130 terrain slope database (IIASA/FAO, 2012) and are based on a high-resolution 90 m SRTM digital elevation model. 131 In each grid cell, we consider reported growing seasons for maize and wheat (Sacks et al., 2010), and spatially 132 explicit nitrogen and phosphorus fertilizer application rates (Mueller et al., 2012).

133 2.1.2 Water erosion equations

134 EPIC includes seven empirical equations to calculate water erosion (Wischmeier and Smith, 1978). The basic 135 equation is:

$$136 Y = R * K * LS * C * P \quad (1)$$

137 where Y is soil erosion in t ha⁻¹ (mass/area), R is the erosivity factor (erosivity unit/area), K is the soil erodibility 138 factor in t MJ⁻¹ (mass/erosivity unit), LS is the slope length and steepness factor (dimensionless), C is the soil 139 cover and management factor (dimensionless) and P is the conservation practices factor (dimensionless).

140 The main difference between the water erosion equations available in EPIC is their energy components used to 141 calculate the erosivity factor. The USLE, RUSLE and RUSLE2 equations use precipitation intensity as an erosive 142 energy to calculate the detachment of soil particles. The Modified Universal Soil Loss Equation (MUSLE) 143 equation and its variations MUST and MUSS use runoff variables to simulate water erosion and sediment yield. 144 The Onstad-Foster equation (AOF) combines energy through rainfall and runoff (Table 1).

145 The erosion energy component is calculated as a function of either runoff volume Q (mm), peak runoff rate q_p 146 (mm h⁻¹) and watershed area WSA (ha), or via the rainfall erosivity index EI (MJ ha⁻¹). The latter determines the 147 detachment of soil particles through the energy of daily precipitation and a statistical estimate of the daily 148 maximum intensity of precipitation falling within 30 minutes. RUSLE2 is the only equation calculating soil 149 deposition. If the sediment load exceeds the transport capacity, determined by a function of flow rate and slope 150 steepness, soil is deposited, which is calculated by a function of flow rate and particle size (USDA-ARC, 2013).

151 The soil cover and management factor is updated for every day where runoff occurs using a function of crop
152 residues, biomass cover and surface roughness. The impact of soil erodibility on simulated water erosion is
153 calculated for the top-soil layer at the start of each simulation year as a function of sand, silt, clay and organic
154 carbon content. The topographic factor is calculated as a function of slope length and slope steepness. A detailed
155 description of the cover and management, soil erodibility and topographic factor is provided in the supporting
156 information (Text S1). The conservation practice factor is included in all equations as a static coefficient ranging
157 between 0 and 1, where 0 represents conservation practices that prevent any erosion and 1 represents no
158 conservation practices. Typical conservation practice factors can be derived from tables, which include values
159 ranging from 0.01 to 0.35 for terracing strategies and from 0.25 to 0.9 for different contouring practices (Morgan,
160 2005; Wischmeier and Smith, 1978). Alternatively, values can be derived from local field studies and remote
161 sensing (Karydas et al., 2009; Panagos et al., 2015), from equations using topographical data (Fu et al., 2005;
162 Terranova et al., 2009), or from economic indicators (Scherer and Pfister, 2015).

163 **2.1.3 Field management scenarios**

164 Field management techniques influencing soil properties and soil cover have a significant impact on the amount
165 of water erosion. However, these methods are very heterogenous around the world and data on different field
166 management techniques are sparse. Therefore, three tillage management scenarios – conventional tillage, reduced
167 tillage and no-tillage – were designed by altering parameters related to water erosion to analyse the impact of field
168 management on simulated water erosion and to draw conclusions on its impact on the quality of simulation results.

169 In the reduced and no-tillage scenarios, we decrease soil disturbance by reducing cultivation operations, tillage
170 depth and surface roughness, and we increase plant residues left in the field after harvest. In addition, we reduce
171 the runoff curve numbers, which indicate the runoff potential of a hydrological soil group, land use and treatment
172 class, with decreasing tillage intensification by using pre-defined values for the cover treatment classes presented
173 in Table 2 (Sharpley and Williams, 1990). By lowering the runoff curve numbers, the impact of reduced tillage
174 practices on the hydrologic balance can be taken into account (Chung et al., 1999). We simulate each tillage
175 scenario with and without green fallow cover in between growing seasons, leading to a total of six field
176 management scenarios.

177 **2.2 Baseline scenario for estimating global water erosion in wheat and maize fields**

178 We estimate the rate of water erosion globally by combining these six tillage and cover crop scenarios in different
179 regions of the world, using climatic and country-specific assumptions and indicators (Table 3). We chose maize
180 and wheat as two contrasting crop types for analysing water erosion in different cultivation systems. Maize is a
181 row crop with relatively large areas of bare and unprotected soil between the crop rows. The plant density in wheat
182 fields is much higher, which improves the protection of soils against water erosion.

183 We consider conventional and reduced tillage systems globally while considering no-tillage only for countries in
184 which the share of conservation agriculture is at least 5 %. In tropical regions, we simulate water erosion with a
185 green cover in between maize and wheat seasons to account for soil cover from a year-round growing season. In
186 temperate and snow regions, we simulate water erosion affected by both soil cover throughout the year and bare
187 soil in winter seasons. In arid regions, we do not simulate green cover in between growing seasons due to the
188 limited water supply.

189 On slopes steeper than 5 %, we consider only rainfed agriculture, as hilly cropland is irrigated predominantly on
190 terraces that prevent water runoff. To account for erosion control measures on steep slopes, we use a conservation
191 P-factor of 0.5 on slopes steeper than 16 %, and a P-factor of 0.15 on slopes steeper than 30 % to simulate
192 contouring and terracing based on the range of P-values presented by Morgan (2005). The threshold for slopes
193 that are cultivated with conservation practices is based on the slope classes used for the underlying structure of
194 slope information of EPIC-IIASA, from which the three highest slope classes (16–30 %, 30–45 %, >45 %) mark
195 slopes that are less likely to be cultivated without measures to prevent erosion. We choose the MUSS equation
196 for the baseline scenario as it generates the lowest deviation between simulated and measured water erosion as
197 discussed below. Table 3 summarises the field management assumptions of the baseline scenario used to aggregate
198 erosion rates in each grid cell and region.

199 **2.3 Uncertainty analysis of field management scenarios and water erosion equations**

200 Given the global scale of the analysis and the aggregated nature of available field management information, there
201 is much uncertainty about crop management strategies, which introduces uncertainty in the water erosion
202 estimates. In addition, each water erosion equation gives a different overall erosion estimate. To discuss the
203 uncertainty of simulation results, we evaluate the variance in simulated water erosion rates at grid level due to: (i)
204 different management assumptions, and (ii) the choice of water erosion equation. The variance of simulation
205 outputs is defined as the range between minimum and maximum simulated water erosion rates with all
206 combinations of tillage and cover crop scenarios and with each water erosion equation.

207 **2.4 Sensitivity analysis of model parameters**

208 We use a sensitivity analysis to identify the most essential input parameters to the factors in the seven water
209 erosion equations. We use the Sobol method (Sobol, 1990), which is a variance-based sensitivity analysis that is
210 popular in environmental modelling (Nossent et al., 2011). With this method, it is possible to quantify the amount
211 of variance that each parameter contributes to the total variance of the model output. These amounts are expressed
212 as sensitivity indices, which rank the importance of each input parameter for simulated water erosion. In addition,
213 the sensitivity indices can be used to determine the impact of parameter interactions on the model output.

214 We test 30 parameters directly connected to the water erosion equations in EPIC. In total, we assign 126,976
215 random values to all input parameters along a pre-defined triangular distribution or a range of discrete values
216 (Table S2). Water erosion is simulated with EPIC using the seven available equations for each random input
217 combination at 40 locations where wheat and maize are cultivated. To represent a heterogenous distribution of
218 global precipitation regimes, we use the natural break optimisation method to choose locations based on average
219 annual precipitation amounts from 1980 to 2010 (Jenks, 1967). For each location and equation, the most sensitive
220 parameters are ranked. To analyse the impact of precipitation regimes on the sensitivity of each parameter, we use
221 Spearman coefficients (ρ) to determine if positive or negative relationships exist between each parameter's
222 sensitivity and annual precipitation.

223 **2.4 Evaluation of simulated erosion against reported field measurements**

224 We compare our simulated water erosion rates with 606 soil erosion measurements on arable land from 36
225 countries representing plot and field scale. Most of the selected erosion rates are based on the ¹³⁷Cs method. In
226 addition, data from erosion plots and volumetric measurements of rills collected by Auerwald et al. (2009),

227 Benaud et al. (2020) and García-Ruiz et al. (2015) are used. In total, 315 records are derived by the ^{137}Cs method,
228 188 records from runoff plots, and 103 records from volumetric measurements of rills. An overview of the field
229 data is presented in Fig. S4-S7, and the full dataset is available in Table S5.

230 Guidance on the ^{137}Cs method is provided by Fulajtar et al. (2017); Mabit et al. (2014) and Zapata (2002). The
231 ^{137}Cs radionuclide was released by nuclear weapon tests and from the accident of the Chernobyl Nuclear Power
232 Plant to the atmosphere and subsequently deposited in the uppermost soil layer by atmospheric fallout. After its
233 deposition it was bind to soil colloids and can be moved only together with soil particles by mechanical processes
234 such as soil erosion. Its chemical mobility and uptake by plants is negligible (Mabit et al., 2014; Zapata, 2002). If
235 part of the topsoil contaminated by ^{137}Cs is removed by erosion, the ^{137}Cs concentrations in soil profiles can be
236 used to trace soil movements using mass balance equation (Walling et al., 2014). A major advantage of the ^{137}Cs
237 method is that it provides long term mean erosion rates (representing the period since ^{137}Cs fallout in the 1960s
238 until the time of sampling) and overcomes the problem of high temporal variability of erosion.

239 Bounded plots are the most commonly used method of erosion measurements. They were introduced in the USA
240 in the 1920s (Hudson, 1993) and were used for the development of USLE and WEPP models (Brazier, 2004).
241 Eroded soil material can be quantified with erosion plots in different ways (total collection of sediment, fractioned
242 collection of sediments using multislot divisors, measurement of discharge and sediment concentration by tipping
243 buckets and Coshocton wheels). The overview of this method is provided by Cerdan et al. (2010); Hudson (1993);
244 Mutchler et al. (1994); De Ploey and Gabriels (1980) and Zachar (1982).

245 The volumetric measurements of rill erosion are used since approximately the 1940s in the USA (Kaiser, 1978 in
246 Evans, 2013) and the 1950s in Europe (Lobotka, 1955), usually at field scale (Boardman, 1990, 2003; Boardman
247 and Evans, 2020; Brazier, 2004; Evans, 2002, 2013; Herweg, 1988; Zachar, 1982). The volume of erosion rills is
248 derived from their lengths and profile cross-section areas, which are measured in field or from terrestrial and aerial
249 photos (Evans, 1986, 1988; Watson and Evans, 1991).

250 The overwhelming effect of the experimental methodology on measured erosion rates, the lack of sufficient
251 metadata accompanying erosion measurements and the granular spatial resolution of our simulation setup hinders
252 a direct comparison between simulated and observed water erosion rates. Instead we compare aggregated
253 simulated and observed erosion values for different slope and precipitation classes to analyse the robustness of
254 simulated water erosion rates under different environmental conditions. Therefore, only measurements with
255 recorded slope steepness and annual precipitation are used. Where annual precipitation is not recorded, it is taken
256 from the WorldClim2 dataset (Fick and Hijmans, 2017). Due to the non-normal distribution of the simulated and
257 measured data, the median deviation (MD) is used as a measure to compare the agreement between simulated and
258 measured water erosion values.

259 **3 Results**

260 We estimate global median water erosion rates of 7 t ha^{-1} and 5 t ha^{-1} in maize and wheat fields, respectively. The
261 total removal of soil in global maize and wheat fields is estimated to be 5.3 Gt a^{-1} and 1.9 Gt a^{-1} , respectively. The
262 map in Figure 2 illustrates the global distribution of simulated water erosion rates. Highest water erosion is
263 simulated in mountainous regions and regions with strong precipitation, especially in tropical climate zones. In
264 Asia, those regions are widespread in the east, south-east and the Himalaya region. In Africa, similar areas with

265 high water erosion values are spread around the continent and are most common at the west coast and in East
266 Africa including broad areas in Guinea, Sierra Leone, Liberia, Ethiopia and Madagascar. In South America,
267 highest water erosion is simulated in the south of Brazil and regions around the Andes mountain range and the
268 Amazon river basin. The highest water erosion values on the American continent are simulated in tropical Central
269 America and the Caribbean. In North America, highest water erosion occurs along the west coast and in the east.
270 Water erosion in Europe is highest in Mediterranean areas and around the Alps.

271 Median annual water erosion values for the five largest wheat and maize producing countries demonstrate the
272 strong impact of climate and topography on simulated water erosion. In Brazil, China and India, where a large
273 proportion of cropland is in tropical areas, water erosion is relatively high with annual median values of 10 t ha⁻¹,
274 6 t ha⁻¹, and 37 t ha⁻¹, respectively. In Russia and the United States annual median values are much lower with 1 t
275 ha⁻¹, and 2 t ha⁻¹, respectively. Overall, Figure 2 illustrates the large variation in simulated water erosion between
276 tropical climate regions and regions with a large proportion of flat and dry land.

277 **3.1 Sources of model uncertainty related to management assumptions and method selection**

278 The uncertainty of the simulation results due to management scenarios and the choice of water erosion equations
279 is highest in regions most vulnerable to water erosion (Figure 3). The annual median uncertainty range at each
280 grid cell due to management is 30 t ha⁻¹. For 97 % of grid cells, the lowest erosion rates are simulated with
281 management scenarios including no-tillage and cover crops. For 86 % of grid cells, maximum erosion rates are
282 simulated under conventional tillage without cover crops. The annual median uncertainty range at each grid cell
283 due to the choice of erosion equation is 23 t ha⁻¹. In 74 % of grid cells, the lowest erosion rates are simulated with
284 the MUSS equation. The highest erosion values are simulated with the RUSLE equation (46 %), followed by the
285 USLE equation (25%).

286 In most locations, the uncertainty due to field management exceeds the uncertainty caused by choice of erosion
287 equation. For 46 % of grid cells, management scenarios cause the prevailing uncertainty, which we defined as the
288 higher uncertainty range by at least 5 t ha⁻¹. The selected erosion equation causes higher uncertainty by at least 5
289 t ha⁻¹ in 14 % of grid cells. The map in Figure 4 illustrates the global distribution of prevailing uncertainty sources.

290 **3.2 Main drivers of the global erosion model**

291 We designed the sensitivity study to explain the large variability of simulated water erosion rates in different
292 regions and to discuss the main differences between water erosion equations. Water erosion is highly sensitive to
293 slope steepness (SLP) for all equations. The first-order sensitivity index of the slope parameter indicates that 46–
294 54 % of the variance in the model output is attributable to the slope, without considering interactions between the
295 input parameters (Table 4). Daily precipitation (PRCP) is the second most important parameter for calculating
296 water erosion, with an individual contribution of around 9–20 % to the variance of the output. The remaining
297 parameters contribute together 4–13 % to the output variance.

298 The first-order sensitivity indices do not include interactions between input parameters, which leads to the sum of
299 all first-order sensitivity indices being lower than 1. The total-order sensitivity indices sum all first-order effects
300 and interactions between parameters, which leads to overlaps in case of interactions and a sum greater than 1. The
301 differences between the first-order and the total-order indices can be used as a measure to determine the impact
302 of the interactions between a specific parameter with other parameters. The total-order sensitivity indices show

303 that slope steepness, including interactions to other parameters, contributes 63–75 % of the output variance from
304 which 18–21 % are due to interactive effects with other parameters (Table 5). The total-order sensitivity indices
305 from precipitation range from 21–36 %, from which 10–18 % is due to interactions with other parameters.

306 The high sensitivity of slope and precipitation is similar for all equations, but the most sensitive parameters after
307 these can be different for each equation. Equations estimating erosion energy by surface runoff and the RUSLE2
308 equation are very sensitive to the hydrological soil group (HSG), which determines the soils infiltration ability.
309 This parameter is used in the calculation of the curve number, which defines the partition of precipitation into
310 runoff and infiltration. Also, the land use number (LUN), which is ranked among the most sensitive input
311 parameters, is used for the calculation of the curve number. The most sensitive parameters of the USLE and
312 RUSLE equation, following slope inclination and daily precipitation, are soil texture classes (SAND & SILT)
313 followed by daily temperature changes (TMX). Crop residues (ORHI) are relatively important for all equations
314 but especially important for equations based on rainfall-energy. Other parameters relevant for field management,
315 such as surface roughness and mixing efficiency of the topsoil, have little influence on water erosion.

316 The sensitivity of slope steepness has a strong positive correlation with the amount of annual precipitation at each
317 location ($\rho = 0.69$, $p < 0.01$). The increase in the sensitivity of slope steepness with increasing annual precipitation
318 is demonstrated in Figure 5, which illustrates substantially lower sensitivity indices at dry locations compared to
319 wet locations. In contrast, the sensitivity indices of daily precipitation are negatively correlated to annual
320 precipitation with a moderate strength ($\rho = 0.45$, $p < 0.05$). Depending on the equation, strong positive or negative
321 correlations between SIs and annual precipitation also exist for other parameters such as slope length, soil texture,
322 soil organic carbon, channel length, channel slope and watershed area (Table S4).

323 **3.3 Evaluation of simulation results against field data**

324 The most recent estimated global water erosion rates on cropland of 11 - 13 t ha⁻¹ derived from a comparable
325 method (Borrelli et al., 2017; Doetterl et al., 2012; van Oost et al., 2007) lie above our simulated median water
326 erosion rates of 7 t ha⁻¹ and 5 t ha⁻¹ for maize and wheat fields, respectively. Similarly, our global water erosion
327 estimates in maize and wheat fields are lower than the median value of 9 t ha⁻¹ from 606 water erosion
328 measurements from cropland around the world.

329 To evaluate the agreement between simulated and observed data, we compare median values between simulated
330 and measured erosion rates grouped by precipitation and slope classes, which are defined along the whole range
331 of recorded slope inclinations and annual precipitation amounts of the field data (Figure 6a). Although slope and
332 precipitation classes from the field are spread unevenly, they cover most climatic and topographic characteristics
333 relevant to global agriculture. The comparison illustrates that the deviation between simulated and field data is
334 highest for locations with steep slopes and high annual precipitation. Where slopes are steeper than 8 % and annual
335 precipitation is higher than 1000 mm, the median of simulated water erosion exceeds the median of measured
336 water erosion in most cases by at least 50 t ha⁻¹. With decreasing slope steepness and annual precipitation, the
337 median deviation between simulated and measured data is decreasing. Where both slope steepness is below 8 %
338 and annual precipitation is below 1000 mm, the median deviation is lower than 5 t ha⁻¹ in most cases. A comparison
339 of measured and simulated water erosion using other equations with the baseline scenario can be found in Fig. S8.

340 The boxplots in Figure 6b illustrate the range of water erosion values measured in the field and simulated with the
341 baseline scenario. The high deviation between observed and simulated values for grouped locations with slopes
342 steeper than 8 % and annual precipitation higher than 1000 mm can also be observed between the range of
343 simulated and measured water erosion values. Outside locations combining steep slopes and strong precipitation,
344 median deviation between simulated and measured data is lower than the variability within the field data. The
345 range of values at locations with lower precipitation and slope steepness demonstrates that simulated values are
346 mostly below measured values in those environments.

347 The uncertainty in the choice of management scenarios and water erosion equations included in our baseline
348 scenario leads to an uncertainty of the deviation between simulated and measured erosion values. This uncertainty
349 is demonstrated in Figure 6b by additional three bars illustrating the range of simulated medians due to contrasting
350 tillage management scenarios, cover crop scenarios and different water erosion equations. At locations with low
351 to moderate slope steepness and annual precipitation, the measured water erosion values agree best with the
352 simulation values generated under scenarios implying larger water erosion, such as high intensity tillage and low
353 soil cover. On the other hand, at locations with steep slopes and intensive precipitation, the measured values are
354 closer to the simulated values under scenarios with less intensive tillage and more soil cover. In addition, the
355 varying sensitivities of each water erosion equation lead to a different magnitude of water erosion values in
356 different environments. On low to moderate slopes, water erosion simulated with the MUSS equation is lowest,
357 whereas RUSLE generates the highest values. On steep slopes, the RUSLE equation generates the lowest water
358 erosion values, which agree best with the measured values. The options to increase and decrease simulated water
359 erosion with different field management scenarios and water erosion equations creates both uncertainty in the
360 model results, but also the possibility to closely match field data.

361 At locations combining steep slopes and intense precipitation, most management scenarios and equations generate
362 water erosion values that are higher than the measured values. However, those environmental conditions cover
363 only a small share of global cropland. Cultivation areas with slopes steeper than 8 % and annual precipitation
364 higher than 1000 mm represent only 7 % of global maize and wheat cropland in our grid cells. The map in Figure
365 7 illustrates that the highest concentration of these areas is in East and South-East Asia, followed by Central and
366 South America, and Sub-Saharan Africa.

367

368 **4 Discussion**

369 **4.1 Varying robustness of simulated water erosion in different global regions**

370 Global water erosion estimates generated with an EPIC-based GGCM and our baseline scenario overlap with
371 observed water erosion values under most of the climatic and topographic environments where maize and wheat
372 are grown. However, global maize and wheat land include locations where environmental characteristics differ
373 significantly from the Midwestern United States, where the data was collected to develop the water erosion
374 equations embedded in EPIC. The USLE model and its modification were developed with data for slopes of up to
375 20 %, which makes model application for steeper slopes uncertain (McCool et al., 1989; Meyer, 1984).
376 Furthermore, the relations between kinetic energy and rainfall energy in the American Great Plains differ from
377 other regions in the world (Roose, 1996). Similarly, the runoff curve number method, which is the key

378 methodology for the calculation of surface runoff, is based on an empirical analysis in watersheds located in the
379 United States and might be less reliable in different regions of the world (Rallison, 1980). Due to the high
380 sensitivity of slope steepness and daily precipitation for the calculation of water erosion, the reliability of the
381 tested equations decreases in regions where typical slope and precipitation patterns differ from the Midwestern
382 US. Although some studies have successfully used USLE and its modification under a different environmental
383 context (e.g. Alewell et al., 2019; Almas and Jamal, 2009; Fischer et al., 2018; Sadeghi and Mizuyama, 2007),
384 many studies have concluded that the accuracy of these models may be reduced outside the environments they
385 were created without calibration and model adaptation (e.g. Cohen et al., 2005; Labrière et al., 2015).

386 The skewed distribution of simulated water erosion values influenced by extreme soil loss rates in few fields
387 highly sensitive to water erosion results in a large difference between the global median value of $6 \text{ t ha}^{-1} \text{ a}^{-1}$ and
388 the global average value of $19 \text{ t ha}^{-1} \text{ a}^{-1}$ (Fig. S9). Due to the strong influence of outliers on average values, we
389 used median values to represent global and regional water erosion rates in wheat and maize fields. The high
390 sensitivity of the simulation results to slope inclinations and precipitation suggests that a significant share of the
391 estimated soil removal of 7.2 Gt a^{-1} originates from small wheat and maize cultivation areas on steep slopes with
392 strong annual precipitation.

393 **4.2 Sources of uncertainties in global water erosion estimates**

394 **4.2.1 Uncertain land use in mountainous regions**

395 Changing climatic conditions with increasing elevation and the variable soils in mountainous regions can favour
396 crop cultivation in higher elevations over lower elevations (Romeo et al., 2015). However, upland farming without
397 soil conservation measures can lead to exhaustive soil erosion and can become a critical problem for agriculture
398 (Montgomery, 2007). Large areas of land have been abandoned due to high erosion rates as soils were no longer
399 able to support crops (Figure 8) (Romeo et al., 2015). As mountain agriculture is determined by various
400 environmental and socio-economic factors, the cultivation of steep slopes can be very variable between regions.
401 Regional erosion assessments in mountainous cropland suggested that areas with extreme water erosion rates are
402 mainly limited to marginal steep land cultivated by smallholders (Haile and Fetene, 2012; Long et al., 2006;
403 Nyssen et al., 2019). In some mountainous regions, efforts to remove marginal farmlands from agricultural
404 production, and programs to improve land management on steep slopes have reduced high water erosion rates
405 (Deng et al., 2012; Nyssen et al., 2015). On the contrary, recent pressure through increasing population and crop
406 production demands has resulted in re-cultivation of hillslopes and a reduction of fallow periods, which limits the
407 recovery of eroded soil (Turkelboom et al., 2008; Valentin et al., 2008).

408 To analyse the sustainability of simulated maize and wheat cultivation systems exposed to high erosion rates, we
409 compare simulated annual eroded soil depth with a global dataset on modelled sedimentary deposit thickness
410 (Pelletier et al., 2016). The comparison shows that at 4 % of grid cells permanent maize and wheat cultivation
411 would not be sustainable as the whole soil profile would be eroded at the end of the simulation period (Fig. S10).
412 Most of the unsustainable agriculture is simulated on steep slopes. Although we account for conservation
413 techniques and cover crops, we do not imitate the highly complex farming practices involving intercropping
414 techniques and fallow periods, which are common on hillslopes typically managed by smallholders (Turkelboom
415 et al., 2008). Moreover, we assume that the slope class representing the largest area in each grid cell most likely
416 represents the largest share of arable land. This builds on the idea that a spatially extensive and diverse landscape

417 can be represented by a single “representative field” characterized by the prevailing topography and soil conditions
418 found in the landscape. On hilly terrain this setup simulates maize and wheat cultivation on steep slopes and thus
419 mainly represents unsustainable agriculture. Although unsustainable maize and wheat cultivation can be observed
420 in several mountain regions, cropland is very heterogeneously distributed in mountains and thus erosion rates
421 from one representative field are highly uncertain.

422 The uncertainty in cropland distribution can partly be reduced by developing a higher resolution global gridded
423 data infrastructure, which is currently not available for EPIC-IIASA. However, due to the large uncertainty in
424 global land cover maps (Fritz et al., 2015; Lesiv et al., 2019), an explicit spatial link between cropland distribution
425 and the corresponding slope category cannot be established without on-site observations. We test the impact of
426 this uncertainty for erosion estimates in Italy, where large maize and wheat cultivation areas are distributed on
427 both flat terrain in the north and mountainous regions in the south. In an ideal scenario where cropland is limited
428 to flattest land available per grid cell, median simulated water erosion in Italy would be reduced to tolerable levels
429 below 1 t ha⁻¹. However, in a scenario, where the most common slopes per grid cell are cultivated, median
430 simulated water erosion increases to 14 t ha⁻¹ due to high water erosion simulated in Italy’s mountainous regions
431 (Fig. S11). This suggests a high uncertainty in global water erosion estimates due to uncertain spatial links between
432 maize and wheat cultivation areas and different slope categories.

433 **4.2.2 Uncertain field management**

434 Simulated water erosion values are highly variable depending on the field management scenario. Simulating cover
435 crop and no-tillage worldwide results in the lowest global soil removal of 2 Gt a⁻¹ with median water erosion rates
436 of 1 t ha⁻¹ a⁻¹ and simulating no cover crops and conventional tillage worldwide results in the highest global soil
437 removal of 13 Gt a⁻¹ with median water erosion rates of 17 t ha⁻¹ a⁻¹. These variations cause further uncertainties
438 in the simulation results.

439 Indeed, a proper reconstruction of a business-as-usual field management is important to further narrow down the
440 uncertainty in global crop modelling (Folberth et al., 2019). In this study we allocated prevailing field management
441 using a set of environmental- and country-specific indicators, similarly to Porwollik et al. (2019). For example,
442 we accounted for conservation agriculture only in countries where this management strategy is likely according
443 to AQUASTAT (FAO, 2016). Furthermore, by assuming cover crops in between wheat and maize seasons we
444 simulated more complex cropping systems in the tropics, where long and year-round growing seasons and frequent
445 multi-cropping farm practices barely leave the soil uncovered. Hence, we did not simulate bare fallow in the
446 tropics as erroneously high water erosion values would have been simulated at locations with heavy precipitation
447 falling on bare soil. In addition, conservation practices such as contouring and terracing are crucial to reduce the
448 simulation of high water erosion values on steep slopes. We simulated these practices for specific slope classes
449 under the assumption that farmers around the world uniformly use conservation practices when cultivating on
450 steep slopes. The most relevant parameters used for tillage scenarios are related to crop residues left in the field.
451 In addition, equations directly connected to surface runoff are strongly influenced by the land use number used to
452 determine the impact of cover type and treatment on soil permeability. While both crop residues and green fallow
453 decrease water erosion significantly, especially in the tropics, their use varies widely between regions and even
454 farms, based on a complex web of factors such as institutional factors, farm sizes, risk attitudes, interest rates,
455 access to markets, farming systems, resource endowments, and farm management skills (Pannell et al., 2014).

456 Also, soil conservation measures such as terraces or contour farming significantly influence water erosion but are
457 very heterogeneously used between regions, farming systems and farmers. Our baseline scenario is a very rough
458 depiction of the complex patterns of field management around the world but attempts to represent these highly
459 influential practices with the limited available data.

460 **4.2.3 Variable estimates from different water erosion equations**

461 The water erosion equation chosen for the baseline scenario generates the lowest global soil removal estimate.
462 Different water erosion equations embedded in EPIC estimate a higher global soil removal of up to 11 Gt a⁻¹ as
463 well as higher median water erosion rates up to 19 t ha⁻¹ a⁻¹. The MUSS water erosion equation chosen for the
464 baseline scenario generates water erosion rates closest to the field data. The focus of equations on either rainfall
465 energy or runoff energy is relevant for the different simulation results under specific environmental conditions.
466 Equations based on rainfall-energy such as RUSLE and USLE simulate higher water erosion values than the other
467 equations at most locations. However, on steep slopes they generate the lowest water erosion values as runoff
468 becomes a greater source of energy than rain with increasing slope steepness (Roose, 1996). Also, the varying
469 sensitivities of other parameters to the equations such as soil properties and management parameters lead to a
470 varying agreement between simulated data and field data depending on the equation selection. Detailed field data
471 would facilitate the choice of an appropriate equation to simulate water erosion worldwide or for a specific region.

472 **4.3 The difficulty of evaluating large-scale erosion estimates with field data**

473 The selection of field data for evaluating simulated water erosion was limited by the low availability of suitable
474 water erosion observations covering the entire globe. The lack of reliable data on water erosion rates is a severe
475 obstacle for understanding erosion, developing and validating models and implementing soil conservation
476 (Boardman, 2006; Nearing et al., 2000; Poesen et al., 2003; Trimble and Crosson, 2000). The main reasons for
477 the low availability of suitable data to evaluate simulated water erosion rates are twofold: (i) erosion monitoring
478 is expensive, time consuming and labour demanding; and, (ii) primary data and metadata of measurement sites
479 accompanying final results are often not available and many older measurements are poorly accessible as they are
480 not available online (Benaud et al., 2020). A variety of factors influencing water erosion such as climate, field
481 topography, soil properties and field management need to be considered when modelling water erosion but are
482 often not reported in available field measurements (García-Ruiz et al., 2015). This hampers a direct comparison
483 between simulated and observed water erosion values. We demonstrated the varying match between measured
484 and simulated water erosion using different tillage and cover crop scenarios. Metadata on field management often
485 only provides the crop cultivated and therefore the conditions under which erosion was measured in the field are
486 not known sufficiently to evaluate erosion values simulated under different field management scenarios. Similarly,
487 information on field topography and soil properties is often not provided with recorded field measurements and
488 thus their use is limited in an evaluation of water erosion estimates simulated in different global environments.
489 Moreover, most data are concentrated in the United States, West Europe and the West Mediterranean (García-
490 Ruiz et al., 2015). In summary, there is a lack of field data representing all needed regions, situations and scenarios
491 (Alewell et al., 2019).

492 The appropriate selection of field data to evaluate model outputs needs to be considered as well. At different
493 spatial scales different erosion processes are dominant and consequently different erosion measurement methods
494 are suitable (Boix-Fayos et al., 2006; Stroosnijder, 2005). Most authors use very heterogeneous data sets to

495 evaluate their models, involving data generated by different methods at variable time and spatial scales and
496 variable quality. For example, Doetterl et al. (2012) used plot data, suspended sediments from rivers, and data
497 from RUSLE modelling. Borrelli et al. (2017) used soil erosion rates (measurement methods are not specified),
498 remote sensing, vegetation index (NDVI) and results of RUSLE modelling. In his review on erosion rates under
499 different land use, Montgomery (2007) used field data derived from erosion plots, field-scale measurements,
500 catchment-scale measurements using hydrological methods, ^{137}Cs -method, soil profile truncation and elevated
501 cemetery plots.

502 Whilst all erosion measurement methods are open to criticism, we decided to use only data obtained by field
503 measurements from runoff plots, by ^{137}Cs method and volumetric surveys as these methods are most suitable at
504 plot, slope and field scale. Geodetic methods such as erosion pins and laser scanner are also used at plot to field
505 scales, but their accuracy is much lower than the accuracy of plot measurements and ^{137}Cs method. Furthermore,
506 erosion pins are mainly suitable for areas with extreme erosion rates (Hsieh et al., 2009; Hudson, 1993), and laser
507 scanners have difficulties to recognize vegetation (Hsieh et al., 2009). Other commonly used methods such as
508 hydrological method (measurements of discharge and suspended sediment load) and bathymetric method are more
509 suitable for larger scales and involve a significant portion of channel erosion, which is not related with agricultural
510 land (García-Ruiz et al., 2015). We did not consider plot experiments using rainfall simulators as they are usually
511 performed on small plots with artificially generated rainfalls, which mostly have very low energies and thus
512 generate low erosion rates (Boix-Fayos et al., 2006; García-Ruiz et al., 2015).

513 The ^{137}Cs method was criticised by Parsons and Foster (2013), who questioned assumptions about the ^{137}Cs
514 behaviour in the environment (variability of the ^{137}Cs input by wet fallout, its microspatial variability at reference
515 sites, its possible mobility in certain soils, the ^{137}Cs uptake by plants and other aspects of ^{137}Cs behaviour in soil).
516 To confront the criticism against the ^{137}Cs method, Mabit et al. (2013) discussed all objections raised by Parsons
517 and Foster (2013) and confirmed its accuracy by listing several studies, in which ^{137}Cs based erosion rates are
518 compared with erosion rates derived from direct measurements. The ^{137}Cs method is based on a set of
519 presumptions which should be met to produce useful results and thus careful interpretation of the obtained results
520 is needed (Fulajtar et al., 2017; Mabit et al., 2014; Zapata, 2002).

521 Similarly, erosion rates obtained by volumetric measurements require careful interpretation as they are exposed
522 to various potential sources of errors and do not account for interill erosion. Although the latter can be neglected
523 under certain circumstances, studies from Europe and semiarid areas of the USA have reported that interill erosion
524 contributed significantly to the amount of soil eroded in fields (Boardman and Evans, 2020; Parsons, 2019).
525 Further, measuring the lengths and cross-sections of rills during field surveys or on terrestrial and aerial photos
526 can be very subjective (Panagos et al., 2016). Different approaches used to detect and measure rills in fields can
527 cause variability in calculated erosion volumes up to a factor of two (Boardman and Evans, 2020; Casali et al.,
528 2006; Watson and Evans, 1991). In order to obtain soil erosion rates in weight units, soil volumes need to be
529 converted using the soil bulk density, which is often based on estimates (Evans and Brazier, 2005).

530 The shortcomings of erosion plot measurements were discussed by several authors (Auerswald et al., 2009;
531 Brazier, 2004; Evans, 1995, 2002; Loughran et al., 1988). Erosion plots have various sizes and shapes (few meters
532 to few hundreds of meters) and various approaches of sediment recording are used (total collection, multislots

533 divisors, tipping buckets, Coshocton wheels), which all involve significant uncertainties. Although some long-
534 term plot experiments exist, many plot measurements fail to cover the whole year erosion cycle (Auerswald et al.,
535 2009). Often, they have to be removed during land management operations such as seeding, ploughing, or they
536 are too expensive and labour demanding.

537 Despite all the shortcomings of available soil erosion data, most data provide valuable information (Benaud et al.,
538 2020). The evaluation against field measurements in this study provided a first indication of the robustness of
539 results under specific topographic and climatic conditions. In most environments relevant for maize and wheat
540 cultivation the deviation between simulated and measured water erosion values is lower than the variability within
541 the field data. The reported data does not enable us to further narrow down the uncertainties addressed. Although
542 the metadata accompanying the field measurements includes information on slope steepness and annual
543 precipitation (or geographic coordinates allowing for overlay with climatic data), information on soil types or
544 texture classes, crop type and tillage system implemented over time are provided only for few points. Also, the
545 various methods used to measure erosion rates, their complex implementation and the bias of field studies towards
546 locations sensitive to erosion lead to an uncertain representation of large-scale erosion rates based on field
547 measurements. To facilitate in-depth evaluation of erosion models across different scales, it is crucial to provide
548 detailed information on site characteristics and to harmonise approaches to measure erosion in the field.

549 **5 Conclusion**

550 The simulation of water erosion with GGCMs is largely influenced by the resolution of global datasets providing
551 topographic, soil, climate, land use and field management data, which is currently not available at the field scale.
552 Yet, considering water erosion in global crop yield projections can provide useful outputs to inform assessments
553 of the potential impacts of erosion on global food production and to identify soil erosion hotspots on cropland for
554 management and policy interventions. To improve the quality of the estimates and to further develop these models,
555 it is crucial to identify, communicate and address the existing uncertainties. Increasing the resolution of global
556 soil, topographic and precipitation data is central for improving global water erosion estimates. In addition, this
557 study provides an insight into the importance of considering field management. The numerous options to simulate
558 the cultivation of fields result in a large range of possible water erosion values, which can only partly be narrowed
559 down at a global scale. Further improvement of global water erosion estimates requires detailed and harmonized
560 field measurements across all environmental conditions to validate and calibrate simulation outputs. Using
561 existing field data, we were able to identify specific environmental characteristics for which we have lower
562 confidence in the modelled erosion rates. These are mainly found in the tropics and mountainous regions due to
563 the high sensitivity of simulated water erosion to slope steepness and precipitation strength, and the complexity
564 of mountain agriculture. However, these areas represent only a small fraction of global cropland for maize and
565 wheat. The overlap of simulated and measured water erosion values in most environments used to produce maize
566 and wheat underlines the robustness of an EPIC-based GGCM to simulate the differences in water erosion rates
567 of major global crop production regions.

568 **Data availability.** Additional information on model outputs, methods, study design and field data are available
569 in the supporting information file: TWCarr-si.zip.

570 **Author contributions.** TC, JB, CF and RS designed the study. TC, JB, CF, EF and RS collected and analysed
571 the data. TC prepared the manuscript with contributions from all co-authors.

572 **Competing interests.** The authors declare that they have no conflict of interest.

573 **Acknowledgement.** This project has received funding from the Grantham Foundation and the European Union's
574 Horizon 2020 research and innovation programme under grant agreement No 776810 (VERIFY) and No 774378
575 (CIRCASA). We would like to thank three anonymous reviewers for their help to improve this paper.

576

577 **References**

578 Alewell, C., Borrelli, P., Meusburger, K. and Panagos, P.: Using the USLE: Chances, challenges and limitations
579 of soil erosion modelling, *Int. Soil Water Conserv. Res.*, 7(3), 203–225, doi:10.1016/j.iswcr.2019.05.004, 2019.

580 Almas, M. and Jamal, T.: Use of RUSLE for Soil Loss Prediction During Different Growth Periods, *Pakistan J.*
581 *Biol. Sci.*, 3(1), 118–121, doi:10.3923/pjbs.2000.118.121, 2009.

582 Auerswald, K., Kainz, M. and Fiener, P.: Soil erosion potential of organic versus conventional farming
583 evaluated by USLE modelling of cropping statistics for agricultural districts in Bavaria, *Soil Use Manag.*, 19(4),
584 305–311, doi:10.1079/sum2003212, 2004.

585 Auerswald, K., Fiener, P. and Dikau, R.: Rates of sheet and rill erosion in Germany - A meta-analysis,
586 *Geomorphology*, 111(3–4), 182–193, doi:10.1016/j.geomorph.2009.04.018, 2009.

587 Balkovič, J., van der Velde, M., Skalský, R., Xiong, W., Folberth, C., Khabarov, N., Smirnov, A., Mueller, N.
588 D. and Obersteiner, M.: Global wheat production potentials and management flexibility under the representative
589 concentration pathways, *Glob. Planet. Change*, 122, 107–121, doi:10.1016/j.gloplacha.2014.08.010, 2014.

590 Balkovič, J., Skalský, R., Folberth, C., Khabarov, N., Schmid, E., Madaras, M., Obersteiner, M. and van der
591 Velde, M.: Impacts and Uncertainties of +2°C of Climate Change and Soil Degradation on European Crop
592 Calorie Supply, *Earth's Futur.*, 6(3), 373–395, doi:10.1002/2017EF000629, 2018.

593 Benaud, P., Anderson, K., Evans, M., Farrow, L., Glendell, M., James, M., Quine, T., Quinton, J., Rawlins, B.,
594 Rickson, J. and Brazier, R.: National-scale geodata describe widespread accelerated soil erosion., *Geoderma*,
595 371(April), 114378, doi:10.1016/j.geoderma.2020.114378, 2020.

596 Den Biggelaar, C., Lal, R., Wiebe, K., Eswaran, H., Breneman, V. and Reich, P.: The Global Impact Of Soil
597 Erosion On Productivity*. II: Effects On Crop Yields And Production Over Time, *Adv. Agron.*, 81(03), 49–95,
598 doi:10.1016/S0065-2113(03)81002-7, 2004.

599 Boardman, J.: Soil erosion on the South Downs: a review, in *Soil Erosion on Agricultural Land*, edited by J.
600 Boardman, I. D. L. Foster, and J. A. Dearing, pp. 87–105, John Wiley & Sons Ltd, Chichester., 1990.

601 Boardman, J.: Soil erosion and flooding on the eastern South Downs, southern England, 1976-2001, *Trans. Inst.*
602 *Br. Geogr.*, 28(2), 176–196, doi:10.1111/1475-5661.00086, 2003.

603 Boardman, J.: Soil erosion science: Reflections on the limitations of current approaches, *Catena*, 68(2–3), 73–
604 86, doi:10.1016/j.catena.2006.03.007, 2006.

605 Boardman, J. and Evans, R.: The measurement, estimation and monitoring of soil erosion by runoff at the field
606 scale: Challenges and possibilities with particular reference to Britain, *Prog. Phys. Geogr.*, 44(1), 31–49,
607 doi:10.1177/0309133319861833, 2020.

608 Boix-Fayos, C., Martínez-Mena, M., Arnau-Rosalén, E., Calvo-Cases, A., Castillo, V. and Albaladejo, J.:
609 Measuring soil erosion by field plots: Understanding the sources of variation, *Earth-Science Rev.*, 78(3–4), 267–
610 285, doi:10.1016/j.earscirev.2006.05.005, 2006.

611 Borrelli, P., Robinson, D. A., Fleischer, L. R., Lugato, E., Ballabio, C., Alewell, C., Meusburger, K., Modugno,
612 S., Schütt, B., Ferro, V., Bagarello, V., Oost, K. Van, Montanarella, L. and Panagos, P.: An assessment of the
613 global impact of 21st century land use change on soil erosion, *Nat. Commun.*, doi:10.1038/s41467-017-02142-

- 614 7, 2017.
- 615 Brazier, R.: Quantifying soil erosion by water in the UK: A review of monitoring and modelling approaches,
616 *Prog. Phys. Geogr.*, 28(3), 340–365, doi:10.1191/0309133304pp415ra, 2004.
- 617 Casali, J., Loizu, J., Campo, M. A., De Santisteban, L. M. and Alvarez-Mozos, J.: Accuracy of methods for field
618 assessment of rill and ephemeral gully erosion, *Catena*, 67, 128–138, 2006.
- 619 Cerdan, O., Govers, G., Le Bissonnais, Y., Van Oost, K., Poesen, J., Saby, N., Gobin, A., Vacca, A., Quinton,
620 J., Auerswald, K., Klik, A., Kwaad, F. J. P. M., Raclot, D., Ionita, I., Rejman, J., Rousseva, S., Muxart, T.,
621 Roxo, M. J. and Dostal, T.: Rates and spatial variations of soil erosion in Europe: A study based on erosion plot
622 data, *Geomorphology*, 122(1–2), 167–177, doi:10.1016/j.geomorph.2010.06.011, 2010.
- 623 CGIAR-CSI: NASA Shuttle Radar Topographic Mission (SRTM). The SRTM data is available as 3 arc second
624 (approx. 90m resolution) DEMs. The dataset is available for download at: <http://srtm.csi.cgiar.org/>, 2006.
- 625 Chappell, A., Baldock, J. and Sanderman, J.: The global significance of omitting soil erosion from soil organic
626 carbon cycling schemes, *Nat. Clim. Chang.*, 6(2), 187–191, doi:10.1038/nclimate2829, 2016.
- 627 Chung, S. W., Gassman, P. W., Kramer, L. A., Williams, J. R., Gu, R. R., Chung, S. W. ;, Gassman, P. W. ;,
628 Kramer, L. A. ; and Williams, J. R. ; Validation of EPIC for Two Watersheds in Southwest Iowa Recommended
629 Citation Validation of EPIC for Two Watersheds in Southwest Iowa, 1999.
- 630 Cohen, M. J., Shepherd, K. D. and Walsh, M. G.: Empirical reformulation of the universal soil loss equation for
631 erosion risk assessment in a tropical watershed, *Geoderma*, 124(3–4), 235–252,
632 doi:10.1016/j.geoderma.2004.05.003, 2005.
- 633 Deng, L., Shangguan, Z. ping and Li, R.: Effects of the grain-for-green program on soil erosion in China, *Int. J.*
634 *Sediment Res.*, 27(1), 120–127, doi:10.1016/S1001-6279(12)60021-3, 2012.
- 635 Doetterl, S., Van Oost, K. and Six, J.: Towards constraining the magnitude of global agricultural sediment and
636 soil organic carbon fluxes, *Earth Surf. Process. Landforms*, 37(6), 642–655, doi:10.1002/esp.3198, 2012.
- 637 Evans, R.: Finding out about water erosion, *Teach. Geogr.*, 12, 17–20, 1986.
- 638 Evans, R.: Water Erosion in England and Wales 1982–1984. Report for Soil Survey and Land Research Centre,
639 Silsoe., 1988.
- 640 Evans, R.: Some methods of directly assessing water erosion of cultivated land – a comparison of measurements
641 made in plots and in fields, *Prog. Phys. Geogr.*, 19, 115–129, 1995.
- 642 Evans, R.: An alternative way to assess water erosion of cultivated land – field-based measurements: An
643 analysis of some results, *Appl. Geogr.*, 22, 187–208, 2002.
- 644 Evans, R.: Assessment and monitoring of accelerated water erosion of cultivated land - when will reality be
645 acknowledged?, *Soil Use Manag.*, 29(1), 105–118, doi:10.1111/sum.12010, 2013.
- 646 Evans, R. and Boardman, J.: The new assessment of soil loss by water erosion in Europe. Panagos P. et al., 2015
647 *Environmental Science & Policy* 54, 438-447-A response, *Environ. Sci. Policy*, 58, 11–15,
648 doi:10.1016/j.envsci.2015.12.013, 2016.
- 649 Evans, R. and Brazier, R.: Evaluation of modelled spatially distributed predictions of soil erosion by water
650 versus field-based assessments, *Environ. Sci. Pol.*, 8, 493–501, 2005.
- 651 FAO/IIASA/ISRIC/ISSCAS/JRC: Harmonized World Soil Database (version 1.1), 2009.
- 652 FAO: AQUASTAT Main Database, [online] Available from:
653 <http://www.fao.org/nr/water/aquastat/data/query/index.html?lang=en> (Accessed 1 July 2020), 2016.
- 654 Fick, S. E. and Hijmans, R. .: Worldclim 2: New 1-km spatial resolution climate surfaces for global land areas,
655 *Int. J. Climatol.*, 2017.
- 656 Fischer, F. K., Kistler, M., Brandhuber, R., Maier, H., Treisch, M. and Auerswald, K.: Validation of official
657 erosion modelling based on high-resolution radar rain data by aerial photo erosion classification, *Earth Surf.*
658 *Process. Landforms*, 43(1), 187–194, doi:10.1002/esp.4216, 2018.
- 659 Fisher, G., Nachtergaele, F., Prieler, S., van Velthuisen, H. T., Verelst, L. and Wiberg, D.: Global Agro-

- 660 ecological Zones Assessment for Agriculture (GAEZ 2007), IIASA, Laxenburg, Austria and FAO, Rome, Italy.,
661 2007.
- 662 Folberth, C., Elliott, J., Müller, C., Balkovič, J., Chryssanthacopoulos, J., Izaurralde, R. C., Jones, C. D.,
663 Khabarov, N., Liu, W., Reddy, A., Schmid, E., Skalský, R., Yang, H., Arneth, A., Ciais, P., Deryng, D.,
664 Lawrence, P. J., Olin, S., Pugh, T. A. M., Ruane, A. C. and Wang, X.: Parameterization-induced uncertainties
665 and impacts of crop management harmonization in a global gridded crop model ensemble, *PLoS One*, 14(9),
666 e0221862, doi:10.1371/journal.pone.0221862, 2019.
- 667 Fritz, S., See, L., McCallum, I., You, L., Bun, A., Moltchanova, E., Duerauer, M., Albrecht, F., Schill, C.,
668 Perger, C., Havlik, P., Mosnier, A., Thornton, P., Wood-Sichra, U., Herrero, M., Becker-Reshef, I., Justice, C.,
669 Hansen, M., Gong, P., Abdel Aziz, S., Cipriani, A., Cumani, R., Cecchi, G., Conchedda, G., Ferreira, S.,
670 Gomez, A., Haffani, M., Kayitakire, F., Malanding, J., Mueller, R., Newby, T., Nonguierma, A., Olusegun, A.,
671 Ortner, S., Rajak, D. R., Rocha, J., Schepaschenko, D., Schepaschenko, M., Terekhov, A., Tiangwa, A.,
672 Vancutsem, C., Vintrou, E., Wenbin, W., van der Velde, M., Dunwoody, A., Kraxner, F. and Obersteiner, M.:
673 Mapping global cropland and field size, *Glob. Chang. Biol.*, 21(5), 1980–1992, doi:10.1111/gcb.12838, 2015.
- 674 Fu, B. J., Zhao, W. W., Chen, L. D., Zhang, Q. J., Lü, Y. H., Gulinck, H. and Poesen, J.: Assessment of soil
675 erosion at large watershed scale using RUSLE and GIS: A case study in the Loess Plateau of China, *L. Degrad.*
676 *Dev.*, 16(1), 73–85, doi:10.1002/ldr.646, 2005.
- 677 Fulajtar, E., Mabit, L., Renschler, C. S. and Lee Zhi Yi, A.: Use of 137Cs for soil erosion assessment, FAO,
678 Rome., 2017.
- 679 García-Ruiz, J. M., Beguería, S., Nadal-Romero, E., González-Hidalgo, J. C., Lana-Renault, N. and Sanjuán, Y.:
680 A meta-analysis of soil erosion rates across the world, *Geomorphology*, 239, 160–173,
681 doi:10.1016/j.geomorph.2015.03.008, 2015.
- 682 Haile, G. W. and Fetene, M.: Assessment of soil erosion hazard in kilie catchment, East Shoa, Ethiopia, L.
683 *Degrad. Dev.*, 23(3), 293–306, doi:10.1002/ldr.1082, 2012.
- 684 Herweg, K.: The applicability of large-scale geomorphological mapping to erosion control and soil conservation
685 in a research area in Tuscany, *Zeitschrift fur Geomorphol. Suppl.*, 68, 175–187, 1988.
- 686 Hsieh, Y. P., Grant, K. T. and Bugna, G. C.: A field method for soil erosion measurements in agricultural and
687 natural lands, *J. Soil Water Conserv.*, 64(6), 374–382, doi:10.2489/jswc.64.6.374, 2009.
- 688 Hudson, N. W.: Field measurement of soil erosion and runoff, Food and Agriculture Organization of the United
689 Nations. [online] Available from: <https://books.google.co.uk/books?id=rS1fiFU3rOwC>, 1993.
- 690 IIASA/FAO: Global Agro-ecological Zones (GAEZ v3.0), IIASA, Laxenburg, Austria and FAO, Rome, Italy.,
691 2012.
- 692 Izaurralde, R. C., Williams, J. R., McGill, W. B., Rosenberg, N. J. and Jakas, M. C. Q.: Simulating soil C
693 dynamics with EPIC: Model description and testing against long-term data, *Ecol. Modell.*, 192(3–4), 362–384,
694 doi:10.1016/j.ecolmodel.2005.07.010, 2006.
- 695 Jenks, G. F.: The Data Model Concept in Statistical Mapping, *Int. Yearb. Cartogr.*, 7, 186–190, 1967.
- 696 Kaiser, J.: Wounding Earth ' s Fragile Skin, *Science* (80-.), 304(June), 1616–1618,
697 doi:10.1126/science.304.5677.1616, 2004.
- 698 Kaiser, V. G.: Annual erosion survey of Whitman county, Washington. 1939/40-1975/76, Spokane, WA 99201.,
699 1978.
- 700 Karydas, C. G., Sekuloska, T. and Silleos, G. N.: Quantification and site-specification of the support practice
701 factor when mapping soil erosion risk associated with olive plantations in the Mediterranean island of Crete,
702 *Environ. Monit. Assess.*, 149(1–4), 19–28, doi:10.1007/s10661-008-0179-8, 2009.
- 703 Kottek, M., Grieser, J., Beck, C., Rudolf, B. and Rubel, F.: World Map of the Köppen-Geiger climate
704 classification updated, *Meteorol. Zeitschrift*, 15(3), 259–263, doi:10.1097/00041433-200208000-00008, 2006.
- 705 Labrière, N., Locatelli, B., Laumonier, Y., Freycon, V. and Bernoux, M.: Soil erosion in the humid tropics: A
706 systematic quantitative review, *Agric. Ecosyst. Environ.*, 203, 127–139, doi:10.1016/j.agee.2015.01.027, 2015.
- 707 Lesiv, M., Laso Bayas, J. C., See, L., Duerauer, M., Dahlia, D., Durando, N., Hazarika, R., Kumar Sahariah, P.,

708 Vakolyuk, M., Blyshchyk, V., Bilous, A., Perez-Hoyos, A., Gengler, S., Prestele, R., Bilous, S., Akhtar, I. ul H.,
709 Singha, K., Choudhury, S. B., Chetri, T., Malek, Ž., Bungnamei, K., Saikia, A., Sahariah, D., Narzary, W.,
710 Danylo, O., Sturn, T., Karner, M., McCallum, I., Schepaschenko, D., Moltchanova, E., Fraisl, D., Moorthy, I.
711 and Fritz, S.: Estimating the global distribution of field size using crowdsourcing, *Glob. Chang. Biol.*, 25(1),
712 174–186, doi:10.1111/gcb.14492, 2019.

713 Lobotka, V.: Terraced fields in Slovakia (In Slovak: Terasove polia na Slovensku), *Agric.*, 2(6), 539–549, 1955.

714 Long, H. L., Heilig, G. K., Wang, J., Li, X. B., Luo, M., Wu, X. Q. and Zhang, M.: Land use and soil erosion in
715 the upper reaches of the Yangtze River: Some socio-economic considerations on China's Grain-for-Green
716 Programme, *L. Degrad. Dev.*, 17(6), 589–603, doi:10.1002/ldr.736, 2006.

717 Loughran, R. J., Elliott, G. L., Campbell, B. L. and Shelly, D. J.: Estimation of soil erosion from caesium-137
718 measurements in a small, cultivated catchment in Australia, *Int. J. Radiat. Appl. Instrumentation. Part*, 39(11),
719 Afshar, F. A., Ayoubi, S., Jalalian, A. (2010)., doi:10.1016/0883-2889(88)90009-3, 1988.

720 Luo, Y., Ahlström, A., Allison, S. D., Batjes, N. H., Brovkin, V., Carvalhais, N., Chappell, A., Ciais, P.,
721 Davidson, E. A., Finzi, A., Georgiou, K., Guenet, B., Hararuk, O., Harden, J. W., He, Y., Hopkins, F., Jiang, L.,
722 Koven, C., Jackson, R. B., Jones, C. D., Lara, M. J., Liang, J., McGuire, A. D., Parton, W., Peng, C., Randerson,
723 J. T., Salazar, A., Sierra, C. A., Smith, M. J., Tian, H., Todd-Brown, K. E. O., Torn, M., van Groenigen, K. J.,
724 Wang, Y. P., West, T. O., Wei, Y., Wieder, W. R., Xia, J., Xu, X., Xu, X. and Zhou, T.: Toward more realistic
725 projections of soil carbon dynamics by Earth system models, *Global Biogeochem. Cycles*, 30(1), 40–56,
726 doi:10.1002/2015GB005239, 2016.

727 Mabit, L., Meusburger, K., Fulajtar, E. and Alewell, C.: The usefulness of ¹³⁷Cs as a tracer for soil erosion
728 assessment: A critical reply to Parsons and Foster (2011), *Earth-Science Rev.*, 127, 300–307,
729 doi:10.1016/j.earscirev.2013.05.008, 2013.

730 Mabit, L., Chhem-Kieth, S., Dornhofer, P., Toloza, A., Benmansour, M., Bernard, C., Fulajtar, E. and Walling,
731 D. E.: ¹³⁷Cs: A widely used and validated medium-term soil tracer, in *Guidelines for using fallout*
732 *radionuclides to assess erosion and effectiveness of soil conservation strategies. IAEA-TECDOC-1741.*, pp. 27–
733 78, IAEA, Vienna., 2014.

734 McCool, D. K., Foster, G. R., Mutchler, C. K. and Meyer, L. D.: Revised slope length factor for the Universal
735 Soil Loss Equation, *Trans. ASAE*, 32, 1571–1576, 1989.

736 McDermid, S. S., Mearns, L. O. and Ruane, A. C.: Representing agriculture in Earth System Models:
737 Approaches and priorities for development, *J. Adv. Model. Earth Syst.*, 9(5), 2230–2265,
738 doi:10.1002/2016MS000749, 2017.

739 Meyer, L. D.: Evolution of the Universal Soil Loss Equation, *J. Soil Water Conserv.*, 39(2), 99–104, 1984.

740 Montgomery, D. R.: Soil erosion and agricultural sustainability., *Proc. Natl. Acad. Sci. U. S. A.*, 104(33),
741 13268–72, doi:10.1073/pnas.0611508104, 2007.

742 Morgan, R. P. C.: *Soil erosion and conservation*, 3rd ed., Blackwell Science Ltd., 2005.

743 Mueller, C., Elliott, J., Chryssanthacopoulos, J., Arneith, A., Balkovic, J., Ciais, P., Deryng, D., Folberth, C.,
744 Glotter, M., Hoek, S., Iizumi, T., Izaurrealde, R. C., Jones, C., Khabarov, N., Lawrence, P., Liu, W., Olin, S.,
745 Pugh, T. A. M., Ray, D. K., Reddy, A., Rosenzweig, C., Ruane, A. C., Sakurai, G., Schmid, E., Skalsky, R.,
746 Song, C. X., Wang, X., De Wit, A. and Yang, H.: Global gridded crop model evaluation: Benchmarking, skills,
747 deficiencies and implications, *Geosci. Model Dev.*, 10(4), 1403–1422, doi:10.5194/gmd-10-1403-2017, 2017.

748 Mueller, N. D., Gerber, J. S., Johnston, M., Ray, D. K., Ramankutty, N. and Foley, J. A.: Closing yield gaps
749 through nutrient and water management, *Nature*, 494(7437), 390–390, doi:10.1038/nature11907, 2012.

750 Mutchler, C. K., Murphree, C. E. and McGregor, K. C.: Laboratory and Field Plots for Erosion Research, in *Soil*
751 *Erosion Research Methods*, edited by R. Lal, p. 352, Routledge., 1994.

752 Nearing, M. A., Romkens, M. J. M., Norton, L. D., Stott, D. E., Rhoton, F. E., Laflen, J. M., Flanagan, D. C.,
753 Alonso, C. V., Binger, R. L., Dabney, S. M., Doering, O. C., Huang, C. H., McGregor, K. C. and Simon, A.:
754 Measurements and models of soil loss rates, *Science (80-)*, 290(5495), 1300–1301, 2000.

755 Nossent, J., Elsen, P. and Bauwens, W.: Sobol' sensitivity analysis of a complex environmental model, *Environ.*
756 *Model. Softw.*, 26(12), 1515–1525, doi:10.1016/j.envsoft.2011.08.010, 2011.

- 757 Nyssen, J., Frankl, A., Zenebe, A., Deckers, J. and Poesen, J.: Land Management in the Northern Ethiopian
758 Highlands: Local and Global Perspectives; Past, Present and Future, *L. Degrad. Dev.*, 26(7), 759–764,
759 doi:10.1002/ldr.2336, 2015.
- 760 Nyssen, J., Tielens, S., Gebreyohannes, T., Araya, T., Teka, K., van de Wauw, J., Degeyndt, K.,
761 Descheemaeker, K., Amare, K., Haile, M., Zenebe, A., Munro, N., Walraevens, K., Gebrehiwot, K., Poesen, J.,
762 Frankl, A., Tsegay, A. and Deckers, J.: Understanding spatial patterns of soils for sustainable agriculture in
763 northern Ethiopia’s tropical mountains., 2019.
- 764 Onstad, C. A. and Foster, G. R.: Erosion modeling on a watershed, *Trans. ASAE*, 18, 288–292, 1975.
- 765 Van Oost, K., Quine, T. A., Govers, G., Gryze, S. De, Six, J., Harden, J. W., Mccarty, G. W., Heckrath, G.,
766 Kosmas, C., Giraldez, J. V and Silva, J. R. M.: The Impact of Agricultural Soil Erosion on the Global Carbon
767 Cycle, *Science* (80-.), 318(5850), 626–629, 2007.
- 768 Panagos, P., Borrelli, P., Meusburger, K., van der Zanden, E. H., Poesen, J. and Alewell, C.: Modelling the
769 effect of support practices (P-factor) on the reduction of soil erosion by water at European scale, *Environ. Sci.*
770 *Policy*, 51, 23–34, doi:10.1016/j.envsci.2015.03.012, 2015.
- 771 Panagos, P., Borrelli, P., Poesen, J., Meusburger, K., Ballabio, C., Lugato, E., Montanarella, L. and Alewell, C.:
772 Reply to “The new assessment of soil loss by water erosion in Europe. Panagos P. et al., 2015 *Environ. Sci.*
773 *Policy* 54, 438–447-A response” by Evans and Boardman [*Environ. Sci. Policy* 58, 11–15], *Environ. Sci. Policy*,
774 59, 53–57, doi:10.1016/j.envsci.2016.02.010, 2016.
- 775 Panagos, P., Standardi, G., Borrelli, P., Lugato, E., Montanarella, L. and Bosello, F.: Cost of agricultural
776 productivity loss due to soil erosion in the European Union: From direct cost evaluation approaches to the use of
777 macroeconomic models, *L. Degrad. Dev.*, 29(3), 471–484, doi:10.1002/ldr.2879, 2018.
- 778 Pannell, D. J., Llewellyn, R. S. and Corbeels, M.: The farm-level economics of conservation agriculture for
779 resource-poor farmers, *Agric. Ecosyst. Environ.*, 187, 52–64, doi:10.1016/j.agee.2013.10.014, 2014.
- 780 Parsons, A.: How reliable are our methods for estimating soil erosion by water?, *Sci. Total Environ.*, 676, 215–
781 221, 2019.
- 782 Parsons, A. J. and Foster, I. D. L.: The assumptions of science. A reply to Mabit et al. (2013)., *Earth-Science*
783 *Rev.*, 127, 308–310, doi:10.1016/j.earscirev.2013.05.011, 2013.
- 784 Pelletier, J. D., Broxton, P. D., Hazenberg, P., Zeng, X., Troch, P. A., Niu, G.-Y., Williams, Z., Brunke, M. A.
785 and Gochis, D.: A gridded global data set of soil, intact regolith, and sedimentary deposit thicknesses for
786 regional and global land surface modeling, *J. Adv. Model. Earth Syst.*, 8(1), 41–65,
787 doi:10.1002/2015MS000526, 2016.
- 788 Pimentel, D.: Soil erosion: A food and environmental threat, *Environ. Dev. Sustain.*, 8(1), 119–137,
789 doi:10.1007/s10668-005-1262-8, 2006.
- 790 Pimentel, D., Harvey, C., Resosudarmo, P., Sinclair, K., Kurz, D., McNair, M., Crist, S., Shpritz, L., Fitton, L.,
791 Saffouri, R. and Blair, R.: Environmental and economic costs of soil erosion and conservation benefits., *Science*
792 (80-.), 267(5201), 1117–1123, doi:10.1126/science.267.5201.1117, 1995.
- 793 De Ploey, J. and Gabriels, D.: Measuring soil loss and experimental studies, in *Soil Erosion*, edited by M. J.
794 Kirkby and R. P. C. Morgan, pp. 63–108, Willey, Chichester., 1980.
- 795 Poesen, J., Nachtergaele, J., Verstraeten, G. and Valentin, C.: Gully erosion and environmental change:
796 Importance and research needs, *Catena*, 50(2–4), 91–133, doi:10.1016/S0341-8162(02)00143-1, 2003.
- 797 Pongratz, J., Dolman, H., Don, A., Erb, K. H., Fuchs, R., Herold, M., Jones, C., Kuemmerle, T., Luysaert, S.,
798 Meyfroidt, P. and Naudts, K.: Models meet data: Challenges and opportunities in implementing land
799 management in Earth system models, *Glob. Chang. Biol.*, 24(4), 1470–1487, doi:10.1111/gcb.13988, 2018.
- 800 Portmann, F. T., Siebert, S. and Döll, P.: MIRCA2000—Global monthly irrigated and rainfed crop areas around
801 the year 2000: A new high-resolution data set for agricultural and hydrological modeling, *Global Biogeochem.*
802 *Cycles*, 24(1), doi:10.1029/2008GB003435, 2010.
- 803 Porwollik, V., Rolinski, S., Heinke, J. and Müller, C.: Generating a rule-based global gridded tillage dataset,
804 *Earth Syst. Sci. Data*, 11(2), 823–843, doi:10.5194/essd-11-823-2019, 2019.

- 805 Rallison, R. E.: Origin and Evolution of the SCS Runoff Equation, in Proceeding of the Symposium on
806 Watershed Management '80 American Society of Civil Engineering Boise ID., 1980.
- 807 Renard, K., Foster, G., Weesies, G., McCool, D. and Yoder, D.: Predicting soil erosion by water: a guide to
808 conservation planning with the Revised Universal Soil Loss Equation (RUSLE), Agric. Handb. No. 703, 404,
809 doi:DC0-16-048938-5 65–100., 1997.
- 810 Romeo, R., Vita, A., Manuelli, S., Zanini, E., Freppaz, M. and Stanchi, S.: Understanding Mountain Soils: A
811 contribution from mountain areas to the International Year of Soils 2015, Rome., 2015.
- 812 Roose, E.: Land husbandry - Components and strategy. 70 FAO soils bulletin, Food and Agriculture
813 Organization of the United Nations, Rome., 1996.
- 814 Ruane, A. C., Goldberg, R. and Chryssanthacopoulos, J.: Climate forcing datasets for agricultural modeling:
815 Merged products for gap-filling and historical climate series estimation, Agric. For. Meteorol., 200, 233–248,
816 doi:10.1016/j.agrformet.2014.09.016, 2015.
- 817 Sacks, W. J., Deryng, D., Foley, J. A. and Ramankutty, N.: Crop planting dates: An analysis of global patterns,
818 Glob. Ecol. Biogeogr., 19(5), 607–620, doi:10.1111/j.1466-8238.2010.00551.x, 2010.
- 819 Sadeghi, S. H. R. and Mizuyama, T.: Applicability of the Modified Universal Soil Loss Equation for prediction
820 of sediment yield in Khanmirza watershed, Iran, Hydrol. Sci. J., 52(5), 1068–1075, doi:10.1623/hysj.52.5.1068,
821 2007.
- 822 Scherer, L. and Pfister, S.: Modelling spatially explicit impacts from phosphorus emissions in agriculture, Int. J.
823 Life Cycle Assess., 20(6), 785–795, doi:10.1007/s11367-015-0880-0, 2015.
- 824 Sharpley, A. N. and Williams, J. R.: EPIC — Erosion / Productivity Impact Calculator: 1. Model
825 Documentation, U.S. Dep. Agric. Tech. Bull., 1768, 235, 1990.
- 826 Skalský, R., Tarasovičová, Z., Balkovič, J., Schmid, E., Fuchs, M., Moltchanova, E., Kindermann, G. and
827 Scholtz, P.: GEO-BENE global database for bio-physical modeling. GEOBENE project. [online] Available
828 from: [http://geo-bene.project-archive.iiasa.ac.at/files/Deliverables/Geo-BeneGlbDb10\(DataDescription\).pdf](http://geo-bene.project-archive.iiasa.ac.at/files/Deliverables/Geo-BeneGlbDb10(DataDescription).pdf),
829 2008.
- 830 Sobol, I. M.: On sensitivity estimation for nonlinear mathematical models, Matem. Mod., 2, 112–118, 1990.
- 831 Stroosnijder, L.: Measurement of erosion: Is it possible?, Catena, 64(2–3), 162–173,
832 doi:10.1016/j.catena.2005.08.004, 2005.
- 833 Terranova, O., Antronico, L., Coscarelli, R. and Iaquina, P.: Soil erosion risk scenarios in the Mediterranean
834 environment using RUSLE and GIS: An application model for Calabria (southern Italy), Geomorphology,
835 112(3–4), 228–245, doi:10.1016/j.geomorph.2009.06.009, 2009.
- 836 Trimble, S. W. and Crosson, P.: U.S. Soil Erosion Rates--Myth and Reality, Science (80-.), 289(5477), 248–
837 250, doi:10.1126/science.289.5477.248, 2000.
- 838 Turkelboom, F., Poesen, J. and Trébuil, G.: The multiple land degradation effects caused by land-use
839 intensification in tropical steepplands: A catchment study from northern Thailand, Catena, 75(1), 102–116,
840 doi:10.1016/j.catena.2008.04.012, 2008.
- 841 UN: Standard Country or Area Codes for Statistical Use (Revision 4). Series M, No. 49/Rev.4, New York.,
842 1999.
- 843 USDA-ARC: Science documentation. Revised Universal Soil Loss Equation, Version 2 (RUSLE 2),
844 Washington, D.C., 2013.
- 845 USGS: USGS 30 ARC-second Global Elevation Data, GTOPO30, 1997.
- 846 Våje, P. I., Singh, B. R. and Lal, R.: Soil Erosion and Nutrient Losses from a Volcanic Ash Soil in Kilimanjaro
847 Region, Tanzania, J. Sustain. Agr., 26(4), 23–42, doi:10.1300/J064v26n04, 2005.
- 848 Valentin, C., Agus, F., Alamban, R., Boosaner, A., Bricquet, J. P., Chaplot, V., de Guzman, T., de Rouw, A.,
849 Janeau, J. L., Orange, D., Phachomphonh, K., Do Duy Phai, Podwojewski, P., Ribolzi, O., Silvera, N.,
850 Subagyono, K., Thiébaux, J. P., Tran Duc Toan and Vadari, T.: Runoff and sediment losses from 27 upland
851 catchments in Southeast Asia: Impact of rapid land use changes and conservation practices, Agric. Ecosyst.

852 Environ., 128(4), 225–238, doi:10.1016/j.agee.2008.06.004, 2008.

853 Walling, D. E. and Webb, B. W.: Erosion and sediment yield: a global overview, IAHS Publ. Proc. Reports-
854 Intern Assoc Hydrol. Sci., 236(236), 3–20 [online] Available from:
855 <http://books.google.com/books?hl=en&lr=&id=bZ-ufVQV5yAC&oi=fnd&pg=PA3&dq=Erosion+and+sediment+yield:+a+global+overview&ots=u-QfIZyy5V&sig=iFyBdzc5dvvd-rF0T35j1jn5EZg>, 1996.

858 Walling, D. E., He, Q. and Zhang, Y.: Conversion Models And Related Software, in Guidelines for Using
859 Fallout Radionuclides to Assess Erosion and Effectiveness of Soil Conservation Strategies, IAEA, Vienna.,
860 2014.

861 Wang, X., Kemanian, A. R., Williams, J. R., Ahuja, L. R. and Ma, L.: Special Features of the EPIC and APEX
862 Modeling Package and Procedures for Parameterization, Calibration, Validation, and Applications, , 16802,
863 doi:10.2134/advagricsystmodel2.c6, 2011.

864 Watson, A. and Evans, R.: A comparison of estimates of soil erosion made in the field and from photographs,
865 Soil Tillage Res., 19, 17–27, 1991.

866 Williams, J. R.: Sediment yield prediction with universal equation on using runoff energy factor., in Present and
867 prospective technology for predicting sediment yields and sources, ARS S-40, pp. 244–252, USDA-ARS,
868 Washington.D.C., 1975.

869 Williams, J. R.: The Erosion-Productivity Impact Calculator (EPIC) Model: A Case History, Philos. Trans. R.
870 Soc. B Biol. Sci., 329(1255), 421–428, doi:10.1098/rstb.1990.0184, 1990.

871 Williams, J. R.: The EPIC model, in Computer Models of Watershed Hydrology, edited by V. P. Singh, pp.
872 909–1000, Water Resources Publications., 1995.

873 Williams, J. R., Izaurralde, R. C. and Steglich, E. M.: Agricultural Policy/Environmental eXtender Model,
874 Theoretical documentation version 0806., 2012.


875 Wischmeier, W. H. and Smith, D. D.: Predicting rainfall erosion losses, Agric. Handb. no. 537, (537), 285–291,
876 doi:10.1029/TR039i002p00285, 1978.

877 Zachar, D.: Soil Erosion, Elsevier, Amsterdam., 1982.

878 Zapata, F.: Handbook for the Assessment of Soil Erosion and Sedimentation Using Environmental
879 Radionuclides, Dordrecht., 2002.


880

881




882

883 Figure 1: Scheme of procedure used for simulating global water erosion with EPIC-IIASA and for analysing the
 884 uncertainty, sensitivity and robustness of our simulation setup.




885

886 Figure 2: Soil loss due to water erosion in maize (a) and wheat (b) fields simulated with the baseline scenario.
 887 Each pixel cell illustrates the median relative water erosion of one representative field. The extent of cropland
 888 areas is not considered in pixel cell size. The bars in the bottom plot (c) illustrate median soil removal for major
 889 world regions simulated under maize and wheat cultivation. The lines and whiskers illustrate 25th and 75th
 890 percentile values. The classification of world regions is illustrated in Fig. S3. Due to the large gap between
 891 aggregated values, all values in the bottom plot have been log-transformed to facilitate the visual comparison.




892

893 Figure 3: Water erosion uncertainty due to (a) field management assumptions and (b) water erosion equations.




894

895 Figure 4: Prevailing uncertainty, defined as the higher uncertainty range by at least 5 t ha⁻¹.




896

897 Figure 5: First-order and total-order sensitivity indices (SI) for (a) slope steepness (%) and (b) precipitation
 898 [mm]. The dashed vertical line illustrates median annual precipitation at all tested locations (1248 mm).



899

900 Figure 6: Comparison of simulated erosion with measured erosion. (a) Median deviation (MD) in $t\ ha^{-1}$ between
 901 simulated erosion using the baseline scenario and measured erosion. Simulated and measured data is grouped
 902 into precipitation classes and slope classes used for the simulation setup. (b) Distributions of measured erosion
 903 rates, erosion rates simulated with the baseline scenario and uncertainty ranges for management assumptions
 904 and erosion equations. The boxplots are defined by the median, the 25th and the 75th percentile of simulated and
 905 measured erosion rates. Whiskers illustrate the 10th and 90th percentile. The three bars next to the boxplots
 906 illustrate minimum and maximum median erosion rates calculated with all tillage and cover crop scenarios and
 907 with all water erosion equations. The values have been log-transformed for better visualization.



908

909 Figure 7: Distribution of low to high slope steepness (SLP) and annual precipitation (PRCP) in maize and wheat
 910 fields. Dark areas illustrate grid cells where dominant slopes are steeper than 8 % and annual precipitation is above
 911 1000 mm. Correspondingly, blue, red, and grey pixels are below one or both thresholds.

(a)



(b)



(c)



(d)



912 Figure 8: (a) Sugar cane cultivation on steep slopes in South China (the steepest slopes are already abandoned
 913 and reforested by eucalyptus trees). (b) Maize cultivation on strongly eroded slopes in South West Uganda. (c)
 914 Abandoned fields and maize cultivation on a slope in South West Uganda. (d) Degraded and abandoned maize
 915 fields in Northern El Salvador.

916

917 Table 1: Equations for calculating the erosivity factor in each water erosion equation available in EPIC.

Erosivity factor	Equation
$R = EI$ (2)	USLE, RUSLE, RUSLE2 (Renard et al., 1997; USDA-ARC, 2013; Wischmeier and Smith, 1978)
$R = 0.646 * EI + 0.45 * (Q * q_p)^{0.33}$ (3)	AOF (Onstad and Foster, 1975)
$R = 1.586 * (Q * q_p)^{0.56} * WSA^{0.12}$ (4)	MUSLE (Williams 1975)
$R = 2.5 * Q * q_p^{0.5}$ (5)	MUST (Williams, 1995)
$R = 0.79 * (Q * q_p)^{0.65} * WSA^{0.009}$ (6)	MUSS (Williams, 1995)

918

919 Table 2: Tillage management scenarios for maize and wheat cultivation

	Conventional tillage	Reduced tillage	No-tillage
total cultivation operations	6 – 7	4 – 5	3
max. surface roughness	30 – 50 mm	20 mm	10 mm
max. tillage depth	150 mm	150 mm	40 – 60 mm
plant residues left	25 %	50 %	75 %
cover treatment class	straight	contoured	contoured & terraced

920

921 Table 3: Management assumptions and erosion equation selected for the baseline scenario

Option	Baseline			
TILLAGE	<ul style="list-style-type: none"> Mix of conventional, reduced and no-tillage in regions where the national share of conservation agriculture is > 5 % according to the latest reported data in AQUASTAT (2007-2014) (FAO, 2016): Argentina, Australia, Bolivia, Brazil, Canada, Chile, China, Colombia, Finland, Italy, Kazakhstan, New Zealand, Paraguay, Spain, USA, Uruguay, Venezuela, Zambia and Zimbabwe. Mix of conventional and reduced tillage in the rest of the world. 			
OFF-SEASON COVER	<ul style="list-style-type: none"> Cultivation only with cover crops in tropics according to Koeppen-Geiger regions (Fig. S1) (Kottek et al., 2006). Mix of off-season cover with and without cover crops in temperate and cold zones. No cover crops in arid regions. 			
CONSERVATION PRACTICE FACTOR	Slope	0 – 16 %	16 – 30 %	> 30 %
	P-Factor	1.0	0.5	0.15
CROP	Water erosion is simulated in wheat and maize fields based on the global crop distribution by MIRCA2000 (Fig. S2) (Portmann et al., 2010).			
IRRIGATION	<ul style="list-style-type: none"> Only on slopes ≤ 5 %. Weighted average of irrigated and rainfed cropland based on MIRCA2000 (Portmann et al., 2010). 			

METHOD	MUSS water erosion equation.
AGGREGATION	Median of all management scenarios per grid cell and region

922

923 Table 4: First-order sensitivity indices (SI) ranking for the five most sensitive input parameters (PARM) for each
924 water erosion equation including slope steepness (SLP), daily precipitation (PRCP), soil hydrologic group (HSG),
925 land use number (LUN), soil silt content (SILT), soil sand content (SAND), curve number parameter (S301),
926 maximum air temperature (TMX) and crop residues left after harvest (ORHI). The sensitivity indices of the
927 remaining parameters are presented in Table S3.

rank	AOF		MUSL		MUSS		MUST		RUSLE2		RUSLE		USLE	
	PARM	SI	PARM	SI	PARM	SI	PARM	SI	PARM	SI	PARM	SI	PARM	SI
1	SLP	0.47	SLP	0.47	SLP	0.46	SLP	0.48	SLP	0.46	SLP	0.50	SLP	0.54
2	PRCP	0.13	PRCP	0.10	PRCP	0.12	PRCP	0.09	PRCP	0.16	PRCP	0.20	PRCP	0.18
3	HSG	0.03	HSG	0.04	HSG	0.05	HSG	0.04	HSG	0.03	SAND	0.05	SILT	0.02
4	SILT	0.02	LUN	0.02	LUN	0.02	LUN	0.02	SAND	0.01	TMX	0.01	TMX	0.01
5	LUN	0.01	SILT	0.02	S301	0.01	SILT	0.02	LUN	0.01	ORHI	0.01	ORHI	0.01
...
sum		0.69		0.68		0.71		0.69		0.71		0.78		0.77

928

929

930 Table 5: Total-order sensitivity indices (SI) ranking for the five most sensitive input parameters (PARM) for each
931 water erosion equation including slope steepness (SLP), daily precipitation (PRCP), soil hydrologic group (HSG),
932 land use number (LUN), soil silt content (SILT), soil sand content (SAND), maximum air temperature (TMX)
933 and crop residues left after harvest (ORHI). The sensitivity indices of the remaining parameters are presented in
934 Table S3.

rank	AOF		MUSL		MUSS		MUST		RUSLE2		RUSLE		USLE	
	PARM	SI	PARM	SI	PARM	SI	PARM	SI	PARM	SI	PARM	SI	PARM	SI
1	SLP	0.68	SLP	0.68	SLP	0.63	SLP	0.68	SLP	0.66	SLP	0.69	SLP	0.75
2	PRCP	0.28	PRCP	0.23	PRCP	0.22	PRCP	0.21	PRCP	0.32	PRCP	0.36	PRCP	0.36
3	HSG	0.09	HSG	0.12	HSG	0.13	HSG	0.12	HSG	0.08	SAND	0.12	SILT	0.05
4	SILT	0.07	LUN	0.07	LUN	0.07	LUN	0.07	LUN	0.05	TMX	0.02	TMX	0.02
5	LUN	0.05	SILT	0.07	SILT	0.05	SILT	0.07	SAND	0.04	ORHI	0.01	SAND	0.01
...
sum		1.29		1.30		1.25		1.27		1.34		1.27		1.27

935