



Predicting the impact of spatial heterogeneity on microbial redox dynamics and nutrient cycling in the subsurface

Swamini Khurana¹, Falk Heße^{2,3}, Anke Hildebrandt^{2,4,5}, Martin Thullner¹

 ¹Department of Environmental Microbiology, Helmholtz Centre for Environmental Research – UFZ, Leipzig, 04318, Germany
 ²Department of Computational Hydrosystems, Helmholtz Centre for Environmental Research – UFZ, Leipzig, 04318, Germany
 ³Institute of Earth and Environmental Sciences, University Potsdam, Potsdam, Germany
 ⁴Institute of Geoscience, Friedrich-Schiller-University Jena, Jena, Germany

10 ⁵German Centre for Integrative Biodiversity Research, Leipzig, Germany

Correspondence: Swamini Khurana (swamini.khurana@ufz.de)

Abstract.

The subsurface is a temporally dynamic and spatially heterogeneous compartment of the Earth's Critical Zone, and biogeochemical transformations taking place in this compartment are crucial for the cycling of

- 15 nutrients. The impact of spatial heterogeneity on such microbially mediated nutrient cycling is not well known which imposes a severe challenge in the prediction of in situ biogeochemical transformation rates and further of nutrient loading contributed by the groundwater to the surface water bodies. Therefore, we undertake a numerical modelling approach to evaluate the sensitivity of groundwater microbial biomass distribution and nutrient cycling to spatial heterogeneity in different scenarios accounting for various
- 20 residence times. The model results gave us an insight into domain characteristics with respect to presence of oxic niches in predominantly anaerobic zones and vice versa depending on the extent of spatial heterogeneity and the flow regime. The obtained results show that microbial abundance, distribution, and activity are sensitive to the applied flow regime and that the mobile (i.e., observable by groundwater sampling) fraction of microbial biomass is a varying, yet only a small, fraction of the total biomass in a
- 25 domain. Furthermore, spatial heterogeneity resulted in anaerobic niches in the domain and shifts of microbial biomass between active and inactive states. The lack of consideration of spatial heterogeneity, thus, can result in inaccurate estimation of microbial activity. In most cases this leads to an overestimation of nutrient removal (up to twice the actual amount) along a flow path. We conclude that the governing factors for evaluating this are the residence time of solutes and the Damköhler number (Da) of the
- 30 biogeochemical reactions in the domain. We propose a relationship to scale the impact of spatial heterogeneity on nutrient removal governed by the log₁₀Da. This relationship may be applied in upscaled descriptions of microbially mediated nutrient cycling dynamics in the subsurface thereby resulting in more accurate predictions of e.g., carbon and nitrogen cycling in groundwater over long periods at the catchment scale.





35 1 Introduction

The Earth's Critical Zone comprises the near surface, surface and sub-surface compartments, from the top of the vegetation canopy to aquifers in the bedrock (Giardino and Houser, 2015;Küsel et al., 2016). Biogeochemical processes impact most ecosystem functions (and consequently ecosystem services) in the Critical Zone by controlling the distribution of nutrients in the compartments of the Critical Zone. All these

- 40 compartments are connected by water fluxes. Within the Critical Zone, the soil and deeper subsurface compartments account for almost 50% of the global carbon budget, and the subsurface is also one of the biggest storage compartments of nitrogen (McMahon and Parnell, 2014;Schlesinger and Andrews, 2000). Especially the subsurface part of the Critical Zone exhibits high spatial and temporal variability in environmental conditions that have been proven to be correlated with subsurface nutrient dynamics (Cole
- 45 et al., 2007;Harden et al., 1997;Holt, 2000;Küsel et al., 2016;van Leeuwen, 2000). Since studies investigating these links are limited to near-surface soil zones, e.g. focusing on the root zone (Küsel et al., 2016), studies linking surficial events with nutrient dynamics in the deeper subsurface are limited. Some research however shows that both, subsurface heterogeneity and input variation, affect subsurface microbial community structure. Schwab et al. (2017) linked changing diversity of microbial communities in
- 50 groundwater with spatio-temporal variation of the groundwater physico-chemical quality. Benk et al. (2019) linked changing composition of dissolved organic matter (DOM) in groundwater with surficial events. Their results also indicated further links with microbial community evolution, but they were unable to resolve the effect of transport in the subsurface presumably due to unresolved spatial heterogeneity. All the aforementioned field scale studies combined establish a link between spatial-temporal variability in
- 55 environmental conditions and nutrient cycling. However, this link is not yet quantitatively characterized. Therefore, this further impedes the predictability of biogeochemical cycles. Improved prediction of biogeochemical cycles requires advancement in mechanistic understanding of governing factors. In this microbial ecosystems play a key role since nearly all the naturally occurring processes that contribute to nutrient cycling, or in general to biogeochemical cycles, are mediated by
- 60 microbial organisms. Recent advances in microbial techniques have led to greater insight into the functions of microbial communities for biogeochemical transformations in laboratory scale batch and column experiments (Ballarini et al., 2014;Grösbacher et al., 2018). However, transferring this knowledge to the subsurface is challenging. For instance, the growth conditions used in laboratory studies are favourable with high substrate concentrations and readily accessible terminal electron acceptors (Grösbacher et al.,
- 65 2018;Hofmann and Griebler, 2018). This is not representative of the subsurface as the subsurface is a spatially heterogeneous medium. Spatial heterogeneity influences subsurface microbial and nutrient dynamics by limiting access to nutrients and electron acceptors (Murphy et al., 1997). Investigating the impact of spatially heterogeneous media on microbial biomass and nutrient cycling in the subsurface is





further hindered by the limited observational opportunities, lack of visualization of real time conditions and limitations of sampling methods and oligotrophic conditions (growth limiting) in groundwater (Ballarini et al., 2014;Hofmann and Griebler, 2018). Since the Critical Zone is a complex system with non-linear process dynamics, governing factors are difficult to isolate, and their impact is unfeasible to quantify (Grösbacher et al., 2018). To overcome these limitations, numerical modelling approaches are powerful alternatives to undertake such investigations (Molins et al., 2014).

- 75 Formulating a conceptual model for microbially mediated carbon and nitrogen dynamics in the subsurface requires a two-pronged approach. First, the reaction network should be representative of the chemical and biological species in question, and second, the flow and transport of the fluid representative of that in the geological domain in question. Biogeochemical reaction networks have been explored sufficiently well over the past decades with improvement in the conceptual understanding of the transient environmental
- 80 conditions of the Critical Zone, the microbial life cycle, and the key processes involved in carbon and nitrogen cycles. Working with microbial explicit models is beneficial as these models could capture transient conditions and associated impacts (Thullner et al., 2007). In contrast to soil-based models that account for complex reaction networks, often comprising more than one microbial functional groups (Yabusaki et al., 2017b;Thullner et al., 2007;Thullner and Regnier, 2019;Manzoni and Porporato, 2009),
- 85 the reaction networks used for modelling biogeochemical processes in deep sub-surface domains are seldom complex. They do not account for microbially explicit models and relevant microbial life processes or any interactions thereof (Thullner and Regnier, 2019). A straight-forward application of the soil-based biogeochemical model approaches to conditions in deeper subsurface compartments is problematic because the nature of carbon source changes as it travels into the deeper zones. A reaction network that is sufficiently
- 90 representative of growth conditions found in the subsurface is lacking and must be conceptualized to study both microbial dynamics and resulting nutrient dynamics. Below we present a possible reaction network for such groundwater setting.

The second challenge, as stated above, is to characterize the flow and transport in a heterogeneous medium. Several attempts have already been made to model microbially driven reactions in the subsurface (Yabusaki

- et al., 2017b;Thullner et al., 2005;Schäfer et al., 1998a;Hunter et al., 1998;Arora et al., 2016) at a regional scale with further investigations on the impact of temporal variation on microbial activity and microbially-driven redox dynamics in riparian zones (Yabusaki et al., 2017a;Dwivedi et al., 2018;Arora et al., 2016). Conducting studies at this scale is relevant but it lacks spatial resolution and does not provide insights into the mechanisms governing microbially mediated nutrient dynamics in the subsurface. Additionally, it is difficult to transfer the results to other geological settings (Tufenkji, 2007).
- To understand the fundamental mechanisms (without the volume averaging effect of large-scale studies) influencing microbial activity, Stolpovsky et al. (2011);Meile and Tuncay (2006);Heße et al. (2010);King





et al. (2010) and Gharasoo et al. (2012) worked on identifying factors influencing microbial activity at the pore scale. Exploring microbial dynamics at the pore scale requires the knowledge of pore scale

- 105 features/geometry for practical applications (Heße et al., 2010), which is typically not available. Additionally, utilizing the pore scale resolution as the base for modelling catchment scale nutrient cycles is computationally problematic. Meanwhile, field groundwater sampling techniques reflect average conditions at the continuum scale depending on sampling resolution. Sanz-Prat et al. (2016) attempted to simplify reactive transport modelling in heterogeneous media at the meter scale by proposing a travel time
- 110 approach, but considered a limited reaction network comprising only growth and decay dynamics of aerobic degraders and denitrifiers. The study conducted by Jung and Meile (2019) applied first-order reactions in heterogeneous porous media at the Darcy scale (or continuum scale) and further upscaled the effective reactions to the regional scale. Microbial kinetics and interplay between different functional groups thereof are more accurately expressed using Monod derived kinetics (Arora et al., 2016;Thullner et al., 2007)
- 115 although Liu et al. (2019) attempt to identify the conditions in which first-order rates may be suitably used in soil systems to optimize computational efforts at field or regional scales. In summary, model attempts have been related to the regional and pore scale, leaving a gap at the soil core, rock core and groundwater sampling scale.
- In this research, we aim to study nutrient dynamics using a comprehensive reaction network at the continuum scale (sub-meter scale in our case). This provides the link between the pore scale microbial dynamics and regional scale microbial dynamics. It assists in developing a process-based understanding of the impact of spatial heterogeneity on microbial activity and subsequent nutrient dynamics and assists in scaling the activity to pragmatic regional scales accounting for spatial heterogeneity. We seek to disentangle the influence of spatial variability of terrestrial subsurface settings (i.e. porous aquifer properties) on the in
- 125 situ biogeochemical function of microorganisms through numerical simulations. We use a complex reaction network that considers varying microbial functional groups (both aerobes and anaerobes), key microbial life processes in a variety of redox conditions (aerobic, ammonia oxidizing, nitrate reducing and sulphate reducing) eventually influencing carbon and nitrogen transformation. Simulated scenarios combine different types of subsurface heterogeneities to determine the resulting biogeochemical potential of the
- 130 subsurface system. The results of this study support the identification of key drivers of microbial dynamics in the Critical Zone and assist in effective upscaling these process descriptions. This, in turn, contributes towards the regional scale modelling of biogeochemical cycles resulting from microbial dynamics.





2 Methods

This study investigates the impact of spatial heterogeneity of the aquifer matrix on nutrient cycling in 135 groundwater with a focus on carbon and nitrogen using reactive transport modelling. For this we used a numerical reactive transport modelling approach which considered the microbial abundance and activity in spatially heterogeneous environmental conditions, that is, spatial variations of aquifer permeability. We used the geochemical and geomicrobial observations from our subject site in the Hainich Critical Zone Exploratory (CZE, Küsel et al. (2016)) as the foundation of the conceptual model to investigate the research

- 140 questions. The subject site was set up under the DFG Collaborative Research Centre Grant 1076 AquaDiva to study the links between surficial processes and subsurface dynamics. Thus, it provides spatially and temporally resolved field observations to enable the formulation of a representative conceptual model. We ran all simulations for a two-dimensional transect of 50 x 30 cm size assuming fully saturated conditions, steady-state flow and constant inflow concentrations of dissolved species. We deemed this domain size
- 145 appropriate to investigate sub-sampling (sub-meter) scale heterogeneities. We considered three different average flow velocities and 12 scenarios of hydraulic conductivity fields of varying heterogeneity for all simulations. The following sections describe the conceptual model comprising reaction network, flow regime and corresponding parameterization, the simulated scenarios and methodology of analyses of the simulation results.


150 2.1 Reaction Network

We conceptualized an extended biogeochemical process network to describe the turnover of carbon and nitrogen (Appendix A and Fig. 1). The reaction network is an extended adaptation of the carbon dynamics described by Vogel et al. (2018), and relevant processes in the subsurface as implemented e.g., by Manzoni and Porporato (2009). The network accounts for autotrophy, and heterotrophy in both aerobic and anaerobic

- 155 regimes considering four functional groups of microorganisms: Aerobic dissolved organic carbon (DOC) degraders, nitrate reducing DOC degraders, ammonium oxidizers and sulphate reducing DOC degraders. The network accounts for other observed microbial processes such as dormancy and mortality using a modified dual-Monod approach adapted from Stolpovsky et al. (2011), and as well as for the "maximum carrying capacity" of the matrix (Ding, 2009;Grösbacher et al., 2018). The latter lumps all growth-limiting
- 160 effects not explicitly accounted for into an additional term (Prommer et al., 1999;Schäfer et al., 1998b;Thullner et al., 2007;Wirtz, 2003). Eventually the carbon and nitrogen loop are completed via recycling of bacterial necro mass. Furthermore, the reaction network accounts for microbial attachment and detachment. Mobile bacteria are transported by the flowing water.







165 Figure 1: Schematic representation of the simulated biochemical reaction network

2.2 Flow and Transport

We modelled steady-state flow conditions in each fully saturated domain (50 x 30 cm in size) by imposing fixed hydraulic heads at the inlet and outlet of the domain adjusting the inlet value to achieve the desired average flow velocity. We kept the head at both, inlet and outlet, constant throughout the simulation periods

170 ensuring steady-state flow conditions. All simulated domains had a constant porosity of 0.2 and an average hydraulic conductivity of 2.0 10⁻⁶ m s⁻¹. The transport regimes account for advection, dispersion and diffusion. We assumed inlet concentrations of mobile species to be constant for all simulations.

2.3 Parameterization

The subject site is a monitoring well transect within the Hainich Critical Zone Exploratory (CZE) in the Hainich National Park, Thuringia, Germany. Groundwater characteristics and composition of microbial communities observed in the groundwater of the subject site over five years (Küsel et al., 2016) informed the parameterization of the model.

As model input, we introduced a solution which was representative of water infiltrating from the shallow subsurface (Table A3), containing a mixture of naturally derived dissolved organic carbon (DOC),

180 dissolved oxygen (DO), nitrate, sulphate and some mobile microorganisms (heterotrophic aerobic degraders, heterotrophic nitrate and sulphate reducers and autotrophic ammonia oxidizers) in the domain. The concentrations of the reactive species mimicked conditions observed in the subject site.





2.4 Simulated Scenarios

185

We performed simulations for three different flow regimes, each characterized by a specific average flow velocity: for the **slow flow** regime, the average flow velocity of $3.8 \ 10^{-4} \text{ m d}^{-1}$ is given by the estimated recharge rate at the subject site (Kohlhepp et al., 2017;Jing et al., 2017) and represents the slow migration of water through the uppermost part of the saturated aquifer. We increased the average flow velocity by a factor of 10 for the **medium flow** regime, and by a factor of 100 for the **fast flow** regime(Table 1).

Property	Slow flow	Medium flow	Fast flow
Darcy velocity (m d ⁻¹)	3.8 10-4	3.8 10-3	3.8 10-2
Diffusion coefficient	8.64 10-5	8.64 10-5	8.64 10-5
$(m^2 d^{-1})$			
Logitudinal dispersivity	0.02	0.02	0.02
(m)			
Length scale (m)	0.1	0.1	0.1
Pe (-)	2.02	11.7	22.45

190 Table 1: Flow and transport parameters considered in the simulations and the resulting Peclet number (Pe) associated with the different flow regimes. For the latter, the domain size of 0.5 m was used as characteristic length for all flow regimes.

For each flow regime, a base case scenario accounted for a homogeneous flow field. Further scenarios considered spatial heterogeneity of the flow field using randomly generated hydraulic conductivity fields (Heße et al., 2014). Each random field was characterized by the same mean value of conductivity (i.e.,

- 195 average conditions at the subject site (Jing et al., 2017)) and correlation length in all realizations. To conceptualize heterogeneity, we used two established geostatistical parameters, variance in the log normal distribution of conductivity and anisotropy, to represent varying porous and fractured media and to also control the degree of channelized flow in the domain. We varied the values of these parameters within ranges reflecting the site conditions/geological features at the study site (Heath, 1983;Kohlhepp et al.,
- 200 2017). The scenarios are summarized in Table 2. In total, we ran 147 simulations for the three different flow regimes in spatially heterogeneous domains. For each scenario we kept the average water fluxes the same in all scenarios, and we compared the results of the scenarios with the base case scenario. We used the breakthrough of a constantly injected conservative tracer as a measure of the solute residence time (i.e., time for flux averaged outlet concentration to reach 50% of inlet value) in the system.

205 2.5 Numerical Tools

We used OGS#BRNS (Centler et al., 2010) to carry out the numerical simulations. This numerical model couples the BRNS (Biochemical Reaction Network Solver (Aguilera et al., 2005;Regnier et al., 2002)), an





established tool that allows for the simulation reaction networks of arbitrary size and complexity (Thullner et al., 2005) with OGS (Open Geosys), a state of the art open source thermo-hydro-mechanical-chemical

210

(THMC) simulator (Kolditz et al., 2012) that has also been used for modelling groundwater flow and transport (Jing et al., 2017). We used a constant finite volume discretization of 0.01 m in both directions. Transient simulations were performed until steady state was achieved.

	Spatial Heterogeneity Cases				
S. No.	Variance in permeability	Anisotropy	Number of realizations	Category type	
1	0	1	1	0:1	
2	0.1	2	4	0.1:2	
3	0.1	5	4	0.1:5	
4	0.1	10	4	0.1:10	
5	1	2	4	1:2	
6	1	5	4	1:5	
7	1	10	4	1:10	
8	5	2	4	5:2	
9	5	5	4	5:5	
10	5	10	4	5:10	
11	10	2	4	10:2	
12	10	5	4	10:5	
13	10	10	4	10:10	

Table 2: Summary of spatially heterogeneous scenarios investigated for each flow regime. S. No. 1 is the homogeneous base215case.

We used the Python programming language (van Rossum and Drake, 2006) (referred to as Python henceforth) to set up the scenarios for running the simulations using OGS#BRNS. These tasks included the generation of input files. We used ogs5py (Müller, 2020) to generate the input files for running the simulations in OGS#BRNS. We used gstools (Müller and Schüler, 2019) to generate the spatial random fields to represent heterogeneous domains in OGS#BRNS. We processed and further analysed simulation

220 fields to represent heterogeneous domains in OGS#BRNS. We processed and further analysed simulation results using a workflow in Python as well. We also used Python to generate all graphical outputs presented in this paper. The scripts used for the Python workflow along with the input files are available in a repository for ease of reproducibility (Khurana et al., 2021).





2.6 Data Analysis

The Peclet number (Pe) indicates the relative importance of flow processes in the flow regime. The resulting Pe of each flow regime (calculated using Eq.(1)) increased from 2 indicating a mixed diffusion-advectiontransport regime for the slow flow regime to 22 indicating fully advection-dominated transport for the fast flow regime (see Table 1 for further details).

$$Pe = \frac{v_{eff} \cdot l}{D + \alpha \cdot v_{eff}},\tag{1}$$

230 with v_{eff} as effective Darcy velocity, l as length scale, D as diffusion coefficient, and α as longitudinal dispersivity.

The breakthrough time is a useful metric to evaluate the matter flux in the domain. We defined the breakthrough time of a conservative tracer as the time taken for the flux averaged concentration at the outlet of the domain to be 50% of the continuous tracer input concentration at the inlet of the domain. This also

235 enables evaluating impact of spatial heterogeneity on matter flux alone, without considering impact of reactions.

To evaluate impact of spatial heterogeneity on nutrient cycling, we calculated removal of reactive species (that is, DOC, DO, ammonium, and nitrate) from the domain. Additionally, to these dissolved reactive species, we also considered (total) nitrogen and total organic carbon (TOC) concentrations by considering

240 also nitrogen and carbon present in the mobile microbial biomass and in particulate organic matter being transported in the domain (Appendix A). We compared the changing mass removal in heterogeneous domains with the respective base case scenarios (homogeneous domains).

To evaluate the key factors determining the impact of spatial heterogeneity on nutrient cycling, we undertook a series of multivariate statistical analyses using Linear Mixed Effect Modelling, progressively

- 245 including variables in both fixed effects and random effects. We compared the Akaike Information Criterion (AIC) of each model to evaluate the fit of the model. With each iteration of the model, we selected the features most influencing the performance of the model and reducing the AIC of the predictions. We described these key factors using established dimensionless numbers which are also identifiable by observations. For example, we used Pe to indicate different flow regimes (described in Sect. 2.4). Similarly,
- 250 we used the Damköhler number (Da) to indicate the reaction regime for each reactive species. Da is defined as the ratio of the advective transport time scale and the reaction time scale. We adapted this definition and used Eq 2 below to calculate the apparent Da using values estimable in the field.

$$Da = \ln \frac{c_{out}}{c_{in}},\tag{2}$$

with C_{in} as flux averaged concentration of a reactive species entering the domain, and C_{out} as flux averaged
 concentration of the reactive species leaving the domain. We took the logarithm of Da to the base 10 (log₁₀Da) to characterize the regime for each reactive species in each domain.





For a scalable relationship addressing impact of spatial heterogeneity on reactive species removal, we conduct a simple linear regression analysis of species removal vs. residence time (both in relative units to the homogeneous reference cases) for different $log_{10}Da$ ranges.

260 For comparison we also use the following expression to predict the impact of reducing breakthrough time on removal of reactive species, in case of a first order removal rate expression (Eq. 3): $C_t = C_i e^{-kt},$ (3)

with C_i as initial concentration of reactive species [ML⁻³], C_t as concentration of reactive species at time t [ML⁻³], k as first order rate constant [T⁻¹], and t as time taken for the reaction to occur [T].

265 Then it follows that, normalized removal of reactive species may be described with:

$$\frac{C_i - C_t}{C_i} = \frac{1 - e^{-kt}}{C_i} \tag{4}$$

To compare the removal of reactive species between two different time points, we use:

Impact on removal of reactive species with respect to base case = $\frac{1 - e^{-Da.tf}}{1 - e^{-Da}}$ (5)

with tf as ratio of the time taken for the reaction to take place in the two (2) different scenarios. In our study,

270 this is same as the ratio of breakthrough time in the heterogeneous domain and that in the base case. Furthermore, we calculated the removal impact of reducing breakthrough time on removal of reactive species, in case of a zeroth order (i.e. constant) removal rate R₀ as
Lement empression of the provided the removal interval in the base case.

Impact on removal of reactive species with respect to base case = $tf R_0$ (6)

3 Results

- 275 We compare characteristics of flow and transport of porous media such as conservative tracer breakthrough, microbial biomass in the domain and nutrient removal from the domain for heterogeneous domains and the base case. The base case is the homogeneous domain in all the three considered flow regimes. We explore flux-averaged concentrations of mobile species and spatially averaged concentrations of immobile species in 1-D, along the predominant flow direction, and explore the 2-D concentration heat maps of the domain
- 280 to compare the information lost when neglecting sub-sampling scale spatial heterogeneity. We further consider the total microbial biomass present in the domain, and nutrient removal from the domain as aggregated results and compare these between the heterogeneous domains and respective base cases.

3.1 Base case (homogeneous domain with uniform flow rate) results

The breakthrough time varied in the base case of each flow regime depending on the flow velocity in the

285 domain. It was 205 days in the slow flow regime, 24 days in the medium flow regime and 2.4 days in the fast flow regime.





As mentioned in Sect. 2.3, we set the concentration of the dissolved species at the inlet to be the same across all flow regimes and heterogeneity scenarios, while it varied at the outlet for each scenario. In all flow regimes DOC concentrations decreased continuously along the domain length, yet they remained at

- 290 relatively high values. In other words, an active microbial DOC degradation in the entire domain was not significantly limited by the abundance of DOC itself. In the slow flow and medium flow regimes, the dissolved oxygen (DO) dropped to concentrations less than 3 µM (common detection limit of DO sensors (ISO, 2014)) within the top half (upgradient) of the domain, indicating anaerobic conditions in the downgradient parts of the domain (Fig. S1). Along the 1-D flow path in the domains aerobic degradation
- rates decreased more and more at low concentrations of oxygen (below approximately 20 μ M), while ammonia oxidation persisted. With DO concentration lowering further, nitrate concentration reduced which is attributable to the activity of nitrate reducers at DO < 15 μ M (Fig. S1). As the concentration of DO reduced, so did the biomass of aerobic degraders, while ammonia oxidizer biomass increased. This resulted in preferential occurrence of ammonia oxidation and nitrate reducers and nitrate reduction further
- 300 downgradient in the domain (Fig. S2). No sulphate reduction took place in any of the flow regimes; the concentration of nitrate was still high (> 63 μ M in all flow regimes) down to the outlet. In contrast to the slow and medium flow regime, DO concentration at the outlet of the fast flow regime (~4 μ M in the base case) indicated aerobic conditions to prevail further downgradient in the domain and consequently the growth of nitrate reducers was suppressed till further downgradient in the domain. Overall, the
- 305 concentration profiles along the flow direction of the base case in all flow regimes were thus in agreement with redox hierarchy wherein aerobic degradation occurred preferentially upgradient in the domain promoted by a relatively high concentration of aerobic degraders. The removal of reactive species, DOC (59.2%), DO (99.6%), ammonium (19.8%) and nitrate (74.7%), was

the highest in the slow flow regime (Table 3). The removal of the reactive species was related to the average

310 flow velocities since it related directly to the residence time in the domain and reaction dominated regimes. Hence, the rate of removal of all these reactive species reduced in medium flow and fast flow regimes. Also the removal of total nitrogen was the highest in the slow flow regime (57%), while the removal of TOC was the lowest there (32.6%) and highest in the medium flow regime (42.6%).

The concentration of microbial species in different states of activity and locations in the domain is shown

- 315 in Table 4. The total biomass concentration was the highest in the slow flow regime (122 μ M C), while it was the lowest in the fast flow regime (86 μ M C). This reduction was mainly attributed to a decrease in mobile biomass concentration with increasing flow rate while the total concentration of immobile biomass remained constant with changing flow regimes. In all the flow regimes, the aerobic degraders formed the dominant species, primarily due to the influx of oxygenated water at nearly saturation levels entering the
- 320 domain at the inlet. In the slow flow regime, the highest proportion of biomass was contributed by inactive





microbial species (>90% of the total biomass concentration). The proportion of active aerobic degraders and ammonia oxidizers was the lowest in the slow flow regime (\sim 5%) while it increased in the medium flow regime (\sim 17%) and it was the dominating species in the fast flow regime (\sim 87%). This was indicative of a small aerobic zone in the slow flow regime domain, which further expanded downgradient in the

- 325 medium flow regime domain (Fig. S1 and Fig. S2). The dominance of the active aerobic degraders and increased presence of ammonia oxidizers in the fast flow regime domain indicated persistent aerobic conditions. Consequently, the proportion of active nitrate reducers was lowest in the fast flow regime (~3%), only growing in the downgradient direction near the outlet of the domain (Fig. S2). The medium flow regime provided the conditions for active nitrate reducers to sustain and form a substantial proportion
- of the microbial community (14% as opposed to ~4% in slow flow regime and ~3% in fast flow regime). Among the active microbial species, the immobile fraction was higher than the mobile fraction in all flow regimes (more than 7 times in the slow flow regime, more than 4 times in the medium flow regime and more than 2 times in the fast flow regime).

Dissolved	Slow flo	W		Medium	flow		Fast flo	W	
Species									
	\dot{m}_{in}	\dot{m}_{out}	$R_b(\%)$	\dot{m}_{in}	\dot{m}_{out}	$R_b(\%)$	\dot{m}_{in}	\dot{m}_{out}	$R_b(\%)$
DOC	0.456	0.186	59.2	4.56	1.98	56.5	45.6	31.4	31.1
DO	0.143	0.001	99.6	1.43	0.01	99.4	14.3	0.2	98.4
Ammonium	0.0342	0.0274	19.8	0.342	0.276	19.4	3.42	3.03	11.5
Nitrate	0.143	0.036	74.7	1.43	0.49	65.8	14.3	14.1	1.12
Nitrogen	0.178	0.077	57.0	1.78	0.84	53.1	17.9	17.6	1.90
TOC	0.470	0.316	32.6	4.70	2.70	42.6	47.0	36.3	22.7

Table 3: Removal of dissolved species (R_b) in terms of mass flux (in in µmol d⁻¹) from the homogeneous domain in three flow regimes - slow flow, medium flow and fast flow

3.2 Tracer breakthrough times

For each flow regime, the tracer breakthrough time in heterogeneous domains varied from that in the base case. With increase in variance of the hydraulic conductivity field, and increasing anisotropy in the domain,

- 340 the breakthrough time was shorter compared to the base case (Fig. 2). This was a result of preferential flow paths that were introduced by the heterogeneous hydraulic conductivity fields. The same "category" (combination of variance and anisotropy) of heterogeneity induced varying impact depending on the flow regime, with higher average flow velocities leading to relatively stronger reductions of the breakthrough times. This difference in the impact of heterogeneity on tracer breakthrough times and thus the residence
- 345 time of solutes in the domain was attributed to the different Peclet numbers (Pe) of the regimes (Table 1).





Diffusion played a stronger role in the transport processes in the slow flow regime, promoting mixing effects and reduced influence of the preferential flow paths in heterogeneous domains. This resulted in the lower deviation in breakthrough time from the base case in the slow flow regime. In contrast, in the medium and in particular in the fast flow regime transport was dominated by advection with little mixing between flow paths. The preferential flow paths in the heterogeneous domains therefore had a higher influence on

the resulting tracer breakthrough times, and thus on the residence time of dissolved species in these regimes.

350

Microbial Species	Slow flow	Medium flow	Fast flow
Total	122.0	93.34	86.35
Active fixed aerobes	3.5	12	74
Active fixed ammonia oxidizers	0.5	2.5	2.4
Active fixed nitrate reducers	2.5	12	2.3
Active mobile aerobes	1.0	2.2	9.6
Active mobile ammonia oxidizers	0.2	0.7	0.7
Active mobile nitrate reducers	1.2	3.1	0.3
Inactive fixed aerobes	44	41	5.2
Inactive fixed ammonia oxidizers	0.5	0.2	0.2
Inactive fixed nitrate reducers	15	11	3.2
Inactive mobile aerobes	24	12	0.5
Inactive mobile ammonia oxidizers	0.3	0.1	0.3
Inactive mobile nitrate reducers	7.9	2.9	1.4

Table 4: Total biomass concentration ($\mu M C$) in homogeneous base case domains (volume averages) with fraction of biomass concentration (%) of each microbial species for three flow regimes

355 **3.3 Distribution of dissolved reactive species in heterogeneous scenarios**

Scenarios with a heterogeneous hydraulic conductivity distribution exhibited a heterogeneous flow velocity distribution with pronounced preferential flow paths emerging with increasing variance and/or anisotropy of the conductivity distributions. The distribution of dissolved species in heterogeneous domains followed the orientation of the preferential flow paths (Fig. S3). All the species persisted longer along these preferential flow paths compared to the low permeability zones. Moreover, also on average all the reactive

360 preferential flow paths compared to the low permeability zones. Moreover, also on average all the reactive species penetrated further downgradient into the heterogeneous domains compared to the homogeneous domain due to the presence of the preferential flow paths (Fig. S1). For example, in the medium and fast flow regime DO persisted further in the heterogeneous domain (deeper in the domain) as the groundwater flowed through preferential flow paths. This impact of heterogeneity on longer persistence of DO was,





365 however, not observable for the slow flow regimes. This is because the DO was preferentially and quickly consumed by aerobic degraders close to the inlet of the domain in the slow flow regime, rendering more than 90% of the domain anaerobic. Effectively, spatial heterogeneity did not play a role in aerobic respiration in the slow flow regime. In contrast, a larger aerobic zone existed in the upgradient section of the domains in medium and fast flow regimes. There, spatial heterogeneity resulted in observable shifts of 370 the transition from aerobic to anaerobic zone to further downgradient parts of the domain.




Figure 2: Breakthrough time in different heterogeneous scenarios (described as variance in permeability field:anisotropy) normalized by that in the base case (or homogeneous case) in three flow regimes: Slow, medium and fast flow.

Because of this delayed transition, nitrate reduction was also affected. In heterogeneous domains, nitrate 375 was observed to be respired further downgradient in the domain and at the interface of high flow and low flow zones (Fig. S3).

These concentration distributions translated into reduced removal of carbon and nitrogen in heterogeneous domains with increasing spatial heterogeneity compared to the base cases (Fig. 3). DOC removal was less than in the base case in all the flow regimes with lowest removal reaching only 40% of the base case values


- 380 in the fast flow regime. The removal of DO was reduced in the fast flow regime (down to 40% of the base case value) while no or negligible reductions were observed for most slow and medium flow scenarios. Nitrogen removal was reduced in the slow and medium flow regimes yet reaching at least 70% of base case values. One exception was nitrogen removal in the fast flow regime, which increased (up to 6 times the base values) compared to the base case. The dependency of TOC removal on spatial heterogeneity matched
- that of DOC for the different flow regimes (Fig. 3).



390



The above results could be summarized by use of $log_{10}D$. The distribution of Da is shown in Fig. S6. The same value of $log_{10}Da$ is associated with different combinations of reaction and flow regimes. The aerobic reactions in the slow flow and the medium flow regimes were characterized with high values of $log_{10}Da$ (>0.5), while the anaerobic reactions in the slow and medium flow regimes were characterized by midrange values of $log_{10}Da$ (0 - 0.5) along with the aerobic reactions in the fast flow regime. The anaerobic reactions in the medium flow regime were characterized by low values (-1 – 0) of $log_{10}Da$. Lastly, the anaerobic reactions in the fast flow regime were characterized by extremely low values of $log_{10}Da$ (<-1).



Residence time of solutes (%)

Figure 3: Nutrient removal in spatially heterogeneous domains in different flow regimes. Values show mass flux differences between inlet and outlet of the heterogeneous domains normalized by the flux differences for the homogeneous base case of each flow regime.

3.4 Distribution of microbial biomass in heterogeneous scenarios

As already shown in Sect. 3.1, the active immobile fraction of the biomass has a larger presence in the domain compared to the mobile fraction, thereby making a larger contribution to nutrient cycling. The
median value of the mobile biomass in the domain varied from 98 μM C (in the fast flow regime) to 320 μM C (in the slow flow regime), out of which, active mobile biomass varied from 8 μM C (in the medium flow regime) to 15 μM C (in the fast flow regime). Immobile biomass in comparison was in the order of





 $300 \ \mu\text{M}$ in all flow regimes, out of which active immobile biomass varied from $29 \ \mu\text{M}$ (in the slow flow regime) to $232 \ \mu\text{M}$ (in the fast flow regime). Therefore, next we focus on the impact of spatial heterogeneity

- 405 on the distribution of this important fraction of the biomass. Aerobic immobile degraders were found to be active and most abundant near the inlet of the domain, and along the preferential flow paths in the downgradient zone of the domain (Fig. S4). Ammonia oxidizers were active at the interfaces between high flow and low flow regions of the upstream parts of the system, co-existing with high concentration of active aerobic degraders. Ammonia oxidizers were also active further downgradient in the system along the
- 410 preferential flow paths. This may be due to the presence of DO at reduced concentrations in the downgradient region of the domain. DO at these concentrations can be preferentially taken up by ammonia oxidizers compared to aerobic degraders. The maximum concentration of active immobile ammonium oxidizers was more than an order of magnitude lower than that of the active immobile aerobic degraders. Nitrate reducers were present in lower permeability zones in the heterogeneous domains, but close to the
- 415 preferential flow paths, in response to the continuous supply of nutrients from the groundwater flowing through the domain. They co-existed with ammonia oxidizers but at higher concentrations. Active immobile nitrate reducers were much higher than active mobile nitrate reducers in the fast and medium flow regimes, but comparable in magnitude in the slow flow regime.
- The corresponding 1-D distribution of microbial species in heterogeneous domains was observed to vary from the base case given the same average water flux (Fig. S2). All the microbial species were prevalent along a larger section in the heterogeneous domains. Aerobic and anaerobic microorganisms also appear to co-exist in heterogeneous domains (solid lines), in contrast to their sequential occurrence in the base case (dashed lines).

The changing distribution pattern of the microbial species impacts the total active immobile biomass

- 425 concentration in the domain, which diverges from the base case as heterogeneity increases (Fig. 4). The biomass of active immobile aerobic degraders decreased with increasing heterogeneity regardless of the flow regime, with lowest values reaching only 40% of the base case biomass. The biomass of immobile active ammonia oxidizers and nitrate reducers also decreased with increasing heterogeneity in slow (~75% and ~90% of base case, respectively) and medium flow regimes (30% and 85% respectively). However, the
- impact on the biomass of immobile active nitrate reducers was the reverse in fast flow regime (increase to 5 times the concentration in the base case). Lastly, there was no impact of spatial heterogeneity in the biomass of immobile active ammonia oxidizers in the fast flow regime.
 Overall, active immobile biomass decreased with increase in spatial heterogeneity in all the flow regimes, while active mobile biomass increased marginally (Fig. S9). Inactive immobile biomass reduced with
- 435 spatial heterogeneity in slow and medium flow regimes, while it increased in the fast flow regime. Lastly, inactive mobile biomass increased with heterogeneity in all flow regimes.





440




Figure 4: Biomass concentration of active immobile fraction of different species in spatially heterogeneous domains in different flow regimes. Shown volume averaged values for the heterogeneous domains were normalized by values of the homogeneous base case of each flow regime.

3.5 Predicting impact of spatial heterogeneity on redox regimes.

To select an appropriate model, multivariate statistical analysis of change in mass removal of reactive species indicated that accounting for the reactive species, in conjunction with flow regime, variance in permeability field and the anisotropy of the domain improved the AIC from 994 (when considering only

- 445 breakthrough time and reactive species) to -211 (all factors above included as random) (Table S1). This indicates that for prediction of nutrient removal it is critical to account for breakthrough time in conjunction with flow regime, spatial heterogeneity, and reactive species. Since nutrient dynamics is influenced by spatial heterogeneity, we may underestimate nutrient removal by 6 times or overestimate it by twice the amount (Fig. 5). We proposed a linear expression to scale the impact of spatial heterogeneity on nutrient
- 450 removal given a regime characterized by \log_{10} Da. The regression parameters informing this expression are given in Table 5.








Figure 5: Regression analysis: Predicting impact of spatial heterogeneity on reactive species removal in different reaction regimes indicated by $log_{10}Da$.

455

Category of flow and	Regressi	Regression parameters				
reaction regime	Slope	Intercept	RMSE			
$log_{10}Da < -1$	-365.0	497.3	57			
$-1 < log_{10}Da < 0$	53.94	46.68	3.7			
$0 < log_{10} Da < 0.5$	12.16	87.71	4.7			
$log_{10}Da > 0.5$	0	100	-			

Table 5: Regression parameters for predicting removal of chemical reactive species based on the reaction regime indicated by log10Da.





4 Discussion

- In this study we synthesized available process knowledge and observations from our subject site into a set of in silico scenarios on the fate of biogeochemically reactive compounds in heterogeneous subsurface settings. This approach allowed us to generate domains capturing the entire range of scenarios, which is not possible experimentally. Therefore, we utilized established geostatistical methods using variance in conductivity field, anisotropy and correlation length to simulate heterogeneous subsurface scenarios. Variance reflects naturally occurring variation in the conductivity field. In case of a high variance, it
- 465 represents scenarios where lenses of a different medium are present in another medium (such as clay lenses in a sandy aquifer). Anisotropy provides an additional control to enforce channelized flow fields in the domain or layering processes in general, common in both alluvial sediments and fractured bedrock. We considered 12 scenarios for representing these heterogeneous flow fields, covering physically (variance) and geometrically (anisotropy) plausible scenarios. This lends confidence to the discussion and applicability
- 470 of the model results.

4.1 Sampling and analysis: Biomass and reactive species

Microbial abundance can be derived from carbon content in the biomass using available conversion factors varying from 5 - 39 femtogram (fg) C/cell (Fukuda et al., 1998;Vrede et al., 2002). This resulted in median values of total mobile biomass in the domain of 10⁹ to 10¹¹ gene copies L⁻¹. Opitz et al. (2014) measured
the total bacterial biomass in groundwater of the subject site to vary from 10⁷ to 10⁹ gene copies L⁻¹ (depending on location, tapped aquifer and season of measurement), which is lower than the simulated mobile values. However, the simulated values of mobile biomass are in the range derived in both lab scale and field scale studies (Holm et al., 1992;Griebler and Lueders, 2009;Grösbacher et al., 2018). Also, the mobile biomass concentration is in the range of particulate organic carbon concentration observed to be

- 480 exported in the seepage at the subject site (Lehmann et al., 2021). It is important to note that the estimated abundance at the site varies with both sampling location and season. We also observe that microbial biomass may be in different states of activity (dormant or active) or location (immobile or mobile) depending on the flow regime and the structure of spatial heterogeneity in the system. This brings into focus that next to spatial heterogeneities addressed in this study also temporal variations of environmental conditions can
- 485 have a significant impact on microbial abundance (Eckert et al., 2015). This study provides preliminary insights into how varying water velocities/flow regimes may impact relative contribution of microbial species between inactive, active, mobile and immobile fractions in spatially heterogeneous domains. A similar trend of response of the system may be expected with temporal fluctuations in groundwater velocities resulting from seasonal cycles. This, however, is not part of the current study.






- 490 Groundwater sampling techniques do not resolve the heterogeneous distribution of chemical and microbial species along the length and cross-section of a well screen. The obtained samples may thus present a skewed/biased observation of the biogeochemical dynamics in the subsurface. For example, the gradual reduction of flux averaged DO concentration from near saturation values at the inlet to below detection limit implies the continuous presence of an aerobic zone until DO is fully depleted. However, when the
- 495 number of oxic and anoxic grid cells were calculated at each cross-section, it was evident that several oxic and anoxic regions can coexist in an apparently oxic zone (Fig. 6). This results in unexpected observations wherein aerobes and anaerobes appear to be active in similar conditions, while in fact, their zones of activity are spatially separated, and anaerobes are active in smaller zones that specifically provide hospitable conditions to their activity. Spatial heterogeneity allows for this apparent co-occurrence of several microbial
- 500 species by providing appropriate niches. For instance, the biomass of immobile active nitrate reducers increased with spatial heterogeneity in the fast flow regime due to the introduction of anaerobic pockets in low flow zones within a predominantly aerobic zone (Fig. S4). Seemingly overlapping conditions have also been observed by field scale studies (Alewell et al., 2006;Waldron et al., 2009;Schwab et al., 2017;Lohmann et al., 2020), although the diversity of microbial communities varied in both space and time.
- 505 Alewell et al. (2006) also noted that small scale heterogeneities did not allow for the sequential redox hierarchy (as defined by energy yields of redox half reactions) to be applicable at the meter scale. We establish that the persistence of microbial species in the domain is governed by the presence of the appropriate carbon source and electron acceptor, despite apparent co-existing microbial species that may be identified by groundwater sampling techniques that do not resolve sub-sampling scale heterogeneities.
- 510 Therefore, while mobility of microbial species using water as the medium may temporarily affect the composition of microbial communities, it is unlikely that mobile microbial species persist in high numbers at a location in absence of sustained sources of nutrient and energy. This is further evident from the impact of spatial heterogeneity on microbial biomass distribution whereby active microbial biomass is only found to be persistent in high numbers in zones where reactive species are easily accessible. In addition, Kim et
- 515 al. (2009) and Kim et al. (2019) also suggested that groundwater redox chemistry and distribution of carbon pools are linked with geological controls such as hydraulic conductivity. The requirement of vertically discretized sampling has already been recognized and addressed by various sampling methodologies such as low flow sampling techniques, passive samplers, point and discrete interval samplers (Powell and Puls, 1993). Our results support the usefulness of such spatially resolved sampling techniques for analysis of
- 520 microbial activity in the groundwater. On the other hand, composite sampling from macro-scale matrix samples is useful to estimate the microbial activity in the sampled matrix core. This enables a more accurate estimate of microbial activity aggregated over the matrix core.







 $\begin{array}{l} \mbox{Figure 6: Comparison of flux averaged DO concentration and % of oxic cells (i.e., cells with DO concentration > 3 \ \mu M) \\ \mbox{3 along the flow direction in a medium flow regime.} \end{array}$

The impact of heterogeneity on microbial biomass distribution has strong implications for evaluating sampling techniques and data obtained from groundwater samples. Immobile microbes account for more microbial activity compared to mobile microbes. However, groundwater samples represent mobile microbial biomass. Estimates of microbial respiration are thereafter made based on the abundance of mobile

- 530 microbes in the obtained groundwater samples. The results of this study suggest that the immobile microbes are, in fact, the major contributors to microbial respiration in the subsurface, which was also experimentally established by (Alfreider et al., 1997;Griebler et al., 2002;Grösbacher et al., 2018) by providing the link between heterogeneous structures in the domain, corresponding nutrient availability and microbial biomass growth. The relative composition of mobile and immobile species is however similar (in part due to the
- 535 same detachment/attachment properties assigned to the microbial species in this study), such that the assessment of microbial diversity based on the mobile fraction, only, would still be representative. However, this is not necessarily the case for nutrient cycling (see below).
 Since spatial heterogeneity impacts microbial biomass distribution and microbial activity, it is not

surprising that spatial heterogeneity also impacts carbon and nitrogen removal. Sanz-Prat et al. (2015, 2016)

540 already established that travel time models are valid for use as reactive transport models in steady-state advective-transport conditions with other studies already discussing the same in surface waters and hyporheic zones (Liao and Cirpka, 2011;Painter, 2018). Painter (2018) also considers the application of





travel time distribution as a representation of heterogeneity to be specific to the processes or reactive species being considered. We further this understanding by exploring a wider range of flow regimes, from locally

- 545 mixed regimes to dominantly advective flow regimes and a complex process network exploring a variety of reactive species across both aerobic and anaerobic microbial processes. The impact on removal of carbon resulting from heterogeneity is consistent for all flow regimes, with carbon removal decreasing in heterogeneous domains. For nitrogen removal the same trend is observed for the slow and medium flow regimes. In contrast, nitrogen removal in the fast flow regime increases with spatial heterogeneity, as
- 550 spatially heterogeneous domains provide the opportunity for anaerobic sub-zones to sustain in predominantly aerobic regimes. As for the fast flow regime aerobic conditions prevailed until the vicinity of the outlet of the simulated domain, nitrogen removal is mainly restricted to such anaerobic sub-zones and heterogeneity leads to an increased number of such subzones. It must be noted though that the concentration of nitrate reduces when and where the concentration of DO is below 15 μM (Fig. S1) (De
- 555 Brabandere et al., 2014;Kalvelage et al., 2013;Seitzinger et al., 2006). The reduced concentration of nitrate is attributable to the activity of nitrate reducers. It is assumed that for sufficiently long domains with anaerobic conditions dominating the downstream parts nitrogen removal would also exhibit a decreasing trend with heterogeneity, even for the fast flow regime. Therefore, travel time information is useful for estimating both carbon and nitrogen removal and identifying dominant microbial redox processes despite
- 560 sub-scale heterogeneities allowing for co-existence of several microbial species. Since immobile active microbial biomass was the major contributor to carbon and nitrogen removal, the reduction in removal of reactive species can be traced to reduced presence of immobile active microbial biomass in heterogeneous domains. In contrast, the contribution of the mobile active biomass in heterogeneous domains remains largely the same as that in homogeneous domains. This indicates that the mobile microbial abundance detected in groundwater samples must be used with care as a proxy for effective microbial activity and nutrient cycling.

4.2 Indicators to evaluate impact of spatial heterogeneity on biomass and redox regimes

In this study, we explored three different flow regimes, representing Peclet (Pe) numbers varying over an order of magnitude. The Damköhler number of the varying components of the system (derived from the

570 observed mass removals and breakthrough times) varies over 4 orders of magnitude (Fig. S6 (a)) in the considered scenarios.

There is substantial overlap in Da across all the flow regimes; a given reactive species has different Da in the different heterogeneous domains in each flow regime. However, spatial heterogeneity impacts the removal of each reactive species in the flow regimes differently. This is further evidenced in the significant

575 improvement of the model AIC (Table S1) when the reactive species is included as a fixed effect in





conjunction with the flow regime. While this approach helps us to generate a predictive understanding of system behaviour, it is specific to reactive species and flow regimes concerned. For a scalable approach to modelling and predicting nutrient cycles at larger scales, it is therefore useful to consider proxy indicators that may assist in generalizing this expression.

- 580 Noting that the impact of spatial heterogeneity on removal of nitrogen in the medium flow regime, and of DO and TOC in the fast flow regime is the same given the same reduction in breakthrough time (Fig. S7), we consider the impact of spatial heterogeneity in context of Da or log₁₀Da, thus providing an opportunity to disentangle reactive species and flow regimes in terms of non-dimensional numbers (Fig. 5). The impact of spatial heterogeneity on nutrient cycling varies with the value of log₁₀Da (Fig. 5). For values higher than
- 585 0.5, the impact is negligible. For \log_{10} Da < -1, spatial heterogeneity results in an increased removal of nutrients from the domain. This is in part due to negligible removal of the corresponding nutrients in the base case (specifically, nitrogen in the fast flow regime, refer to Sect. 3.3 and 4.1). Even a marginal increase in the relevant microbial activity results in a remarkably high impact on the removal of the corresponding nutrient when compared to the base case. As discussed above, for the fast flow regime aerobic conditions
- 590 are found along the entire homogeneous domain. Since most nitrogen removal processes are suppressed by elevated DO concentrations, the formation of an anaerobic zone in low flow regions of the heterogeneous domains is the only chance of these nitrogen removal processes to take place in the fast flow scenarios. The observed increase in mass removal with heterogeneity is thus to some extent an artefact that may not represent a general trend. While heterogeneity does have an impact on nitrogen removal in the fast flow
- 595 regime, even after increased removal, the log₁₀Da value remains below -1, indicating low absolute activity/removal.

For regimes where $log_{10}Da > 0.5$, spatial heterogeneity has limited impact on the ability of the system to remove reactive species. But, removal of reactive species decreases with reduction in breakthrough time for $-1 < log_{10}Da < 0.5$. To explore the cause of this, we compared the trend of removal of reactive species

- 600 in first order rates (Fig. S8) and zero order rates with reduced residence times with the simulation results for varying values of \log_{10} Da. The mean of \log_{10} Da in this regime was -0.3 with a standard deviation of 0.3. So, we approximated the analytical solution for varying values of \log_{10} Da (Fig. S8). With increasing \log_{10} Da (between 0 and 0.5), the root mean squared error (RMSE) between the analytical solution for a first order reaction and the simulation results decreases. Additionally, the data points lie in between the solutions
- for first order and zero order kinetics, as it would be the case for Monod kinetics in case of reduced residence times. Consequently, the impact of spatial heterogeneity on regimes with $0 < \log_{10}Da < 0.5$ may be described on the bases of reducing residence time alone and the results do not allow to determine if additional heterogeneity effects on removal take place. For regimes where $-1 < \log_{10}Da < 0$, first order kinetics approximate towards zero order kinetics. Additionally, the impact on mass removal of reactive





- 610 species in this domain is lower than estimated from the analytical solution. Therefore, while mass removal of reactive species reduces with reducing breakthrough times, it does not follow Monod kinetics which implies that heterogeneity has a different impact on removal than changing only the residence time. In fact, the impact of spatial heterogeneity on mass removal is lower than that predicted by reducing residence time alone. For a quantitative assessment we proposed linear regression metrics to estimate mass removal
- 615 resulting from reducing residence times. At the same time, we observed that the dramatic increase in mass removal for regimes \log_{10} Da < -1 is not attributable to a shorter residence time, but due to heterogeneous conditions providing niches to the relevant microbial species to become active. Therefore, we conclude that spatial heterogeneity may result in changed nutrient dynamics. The regression model allows to link the impact of heterogeneity to variables which can be estimated in field studies. Furthermore, this helps to
- 620 categorize reaction regimes to consider if spatial heterogeneity is of significance. For high log₁₀Da values, spatial heterogeneity is not of significance. For extremely low log₁₀Da values, spatial heterogeneity resulted for the used model domains in a high impact on removal rates with respect to the homogeneous base cases. However, this might be an artifact of the used domain size and the absolute removal values are still low. Thus, heterogeneity effects may be neglected for these low log₁₀Da values. In turn, spatial heterogeneity is
- significant for medium range \log_{10} Da values (-1 < \log_{10} Da < 0.5). For these values, the highest heterogeneity induced reductions in mass removal were observed and can be well described by the linear regression model.

5 Summary and Conclusions

- In this study, we investigated the impact of spatial heterogeneity on biomass persistence, distribution, and nutrient cycling in the subsurface. When considering spatial heterogeneity, a combination of variance and anisotropy of the hydraulic conductivity was considered for when evaluating the transport regime, which may be further interpreted as a reduction of solute residence time in the domain. The flow regime was found to play an influential role in the average behaviour of the domain. Not only does the total microbial biomass vary with the flow regime, but the contribution of different fractions of microbial biomass (between active
- 635 or dormant, mobile or immobile) is also different based on the flow regime. Spatial heterogeneity also impacts the different fractions of microbial biomass differently. This has a cumulative impact on nutrient cycling in the subsurface. The activity of the microbial species in the domain is governed by the spatial heterogeneity as it influences the distribution of nutrients and energy sources. We found that several microbial species that are conventionally accepted to occupy mutually exclusive niches may co-exist in the
- 640 subsurface in close vicinity. This further demonstrates that the occurrence of aerobic conditions does not preclude the existence of anaerobic species in the same zone as heterogeneity leads to the formation of





anaerobic regions within an aerobic zone. Since modelers and experimentalists do not conventionally resolve these small-scale heterogeneities the accuracy of the prediction of biogeochemical cycles at the larger scale suffers.

- 645 Depending on the reaction and flow regime of the domain, the impact of spatial heterogeneity on mass removal of reactive species can be quantified as a linear function of the breakthrough time. We propose the use of the Damköhler number to identify the appropriate parameters of this function. Simulations that neglect or aggregate microbially mediated dynamics in spatially heterogeneous media may overestimate reactive species removal by as much as 2 times. This factor can be predicted using readily observable data
- 650 that informs Damköhler numbers and residence times using a linear function of residence time. We propose using this scaling factor to account for heterogeneity in regional scale simulations for accurate prediction of microbial mediated reactive species dynamics in groundwater.

Appendix A: Biochemical reaction network

A.1 Reactive Species

- 655 1. Chemical compounds:
 - a. Dissolved Organic Carbon (DOC)
 - b. Particulate Organic Carbon (POC)
 - c. Oxygen (O2)
 - d. Nitrate (NO3)
- 660
- e. Sulphate (SO4)
- f. Ammonium (NH4)
- 2. Microbial species:
 - a. Aerobic DOC degraders (BO2)
 - b. Nitrate reducers (BNO3)c. Sulphate reducers (BSO4)
- 665

670

d. Ammonia oxidizers (BNH4)

For each microbial species, we considered different subpopulations: active bacteria able to grow and to perform biogeochemical reactions, inactive bacteria, immobile bacteria attached to the solid matrix, mobile bacteria moving with the flowing water. In combination this leads to four subpopulations for each microbial species X: active immobile $(X_{a,s})$, active mobile $(X_{a,w})$, inactive immobile $(X_{i,s})$ and inactive mobile $(X_{i,w})$.

A.2. Biogeochemical Reactions

Aerobic respiration: $CH_2O + O_2 \rightarrow HCO_3^- + H^+$ (A1)





Nitrate reduction:
$$CH_2O + 0.8NO_3^- + 0.8H^+ \rightarrow HCO_3^- + 0.4N_2 + 0.4H_2O + H^+$$
 (A2)

Sulphate reduction:
$$CH_2O + 0.5SO_4^{2-} + H^+ \to HCO_3^- + 0.5HS^- + 1.5H^+$$
 (A3)

675 Ammonia oxidation:
$$0.5NH_4^+ + O_2 \rightarrow 0.5NO_3^- + 0.5H_2O + H^+$$
 (A4)

Hydrolysis of POC:
$$C_{10}H_7O_2N + 8H_2O + H^+ \rightarrow 10CH_2O + NH_4^+$$
 (A5)

A.3. Rate expressions:

A.3.1 Microbial respiration

We used modified Monod-type expressions for microbially driven reactions:

680 1. Aerobic respiration:

$$r = \frac{kmax1 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{O2}{ksox+O2}\right)}{\frac{doxmin-kmax1 \times \left(\frac{ksodoc+DOC}{ksoax+OC}\right) \times \left(\frac{O2}{ksox+O2}\right)}{st \times doxmin}} \left(BO2_{a,s} + BO2_{a,w}\right)$$
(A6)

2. Nitrate reduction:

$$r = \frac{kmax2 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{NO3}{ksno3+NO3}\right) \times \left(\frac{kindox}{kindox+O2}\right)}{\frac{no3min-kmax2 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{NO3}{ksno3+NO3}\right) \times \left(\frac{kindox}{kindox+O2}\right)}{st \times no3min}} \left(BNO3_{a,s} + BNO3_{a,w}\right)$$
(A7)

3. Sulphate reduction:

$$685 r = \frac{kmax3 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{SO4}{ksso4+SO4}\right) \times \left(\frac{kindox}{kindox+O2}\right) \times \left(\frac{kinno3}{kinno3+NO3}\right)}{\frac{so4min-kmax3 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{SO4}{ksso4+SO4}\right) \times \left(\frac{kindox}{kindox+O2}\right) \times \left(\frac{kinno3}{kinno3+NO3}\right)}{st x so4min}} \left(BSO4_{a,s} + BSO4_{a,w}\right)$$
(A8)

4. Ammonia oxidation:

$$r = \frac{kmax4 \times \left(\frac{O2}{ksox+O2}\right) \times \left(\frac{NH4}{ksamm+NH4}\right)}{\frac{nh4min-kmax4 \times \left(\left(\frac{O2}{ksox+O2}\right)\right) \times \left(\frac{NH4}{ksamm+NH4}\right)}{st \times nh4min} + 1} \left(BNH4_{a,s} + BNH4_{a,w}\right)$$
(A9)

A.3.2 Microbial growth

Growth processes (i.e. formation of biomass carbon) are linked to rates of microbially driven reactions using a constant yield factor with an additional dependency on the concentration of ammonium, and its availability for uptake. For the latter, we considered a fixed ratio between carbon (DOC) and nitrogen (NH4) uptake.

1. Dependency on ammonium:

$$NH4limit = \frac{1}{e^{\frac{amming - NH4}{st \times amming}} + 1}}$$
(A10)

695 2. Active aerobic DOC degraders:

$$r = NH4 limit \times \frac{kmax1 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{O2}{ksox+O2}\right)}{\frac{DOC}{e} e^{\frac{O2min-kmax1 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{O2}{ksox+O2}\right)}{st \times O2min} + 1}} Y_o \times BO2_{a,x}$$
(A11)





with a = active biomass, x=s for attached and x=w for mobile bacteria

3. Active nitrate reducers:

$$r = NH4 limit \times \frac{kmax2 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{NO3}{ksn03+NO3}\right) \times \left(\frac{kindox}{kindox+O2}\right)}{\frac{DOC}{e} \times \left(\frac{NO3}{ksn03+NO3}\right) \times \left(\frac{kindox}{kindox+O2}\right)}{st \times no3min} Yn \times BNO3_{a,x}$$
(A12)

700 4. Active sulphate reducers:

$$r = NH4limit \times \frac{kmax3 \times \left(\frac{DOC}{ksodoc+DOC}\right) \times \left(\frac{SO4}{ksods+SO4}\right) \times \left(\frac{kindox}{kindox+O2}\right) \times \left(\frac{kinno3}{kinno3+NO3}\right)}{e^{\frac{SO4}{e} \times \left(\frac{kindox}{ksods+CDOC}\right) \times \left(\frac{kindox}{ksods+SO4}\right) \times \left(\frac{kinno3}{kindox+O2}\right) \times \left(\frac{kinno3}{kinno3+NO3}\right)}_{st \times so4min}} Y_{s} \times BSO4_{a,x}$$
(A13)

5. Active ammonia oxidizers:

$$r = NH4 limit \times \frac{kmax4 \times \left(\frac{O2}{ksox+O2}\right) \times \left(\frac{NH4}{ksamm+NH4}\right)}{\frac{nh4min-kmax4 \times \left(\left(\frac{O2}{ksox+O2}\right)\right) \times \left(\frac{NH4}{ksamm+NH4}\right)}{st \times nh4min}} Ya \times BNH4_{a,x}$$
(A14)

705 A.3.3 Processes governing the location of the microbes

1. Mobilization of immobilized bacteria (Bxx) into the fluid medium (i.e. the transfer of attached bacteria into mobile bacteria) are adapted from (Rittman and McCarty (2001)) assuming additionally that high total attached biomasses lead to higher detachment rates (adapted from Clément et al. (1997)):

$$r = kl \times (vq0 \times vpor0)^{0.58} \times Bxx +$$

$$\frac{kdet}{e^{Bfmax-Bo2_{a,s}-BO2_{i,s}-BNO3_{a,s}-BSO4_{a,s}-BSO4_{i,s}-BNH4_{a,s}-BNH4_{i,s}}}_{st \times Bfmax} \times Bxx$$
(A15)

2. Immobilization or reattachment: Attachment rates of mobile bacteria Byy is also depending on the total concentration of attached biomass:

$$r = katt \times \left(1 - \frac{1}{e^{\frac{Bfmax - Bo2_{a,s} - BO2_{i,s} - BNO3_{a,s} - BSO4_{a,s} - BSO4_{i,s} - BNH4_{a,s} - BNH4_{i,s}}}{st \times Bfmax}}\right) \times Byy$$
(A16)

A.3.4 Processes governing the activity states of microbes:

715 1. Deactivation/Dormancy: Deactivation rates of active bacteria (i.e., conversion of active (mobile/attached) into inactive or dormant (mobile/attached) bacteria) at unfavourable substrate conditions are expressed following Stolpovsky et al. (2011).

$$r = kdeac \times Bxx \times (1 - \frac{1}{e^{\frac{Kxx}{st}} + 1})$$
(A17)

with the term Kxx depending on the bacterial species Byy and its substrate source (see Table A1).

720





	Descriptors			
Notation	Aerobic degraders	Nitrate reducers	Sulphate reducers	Ammonia oxidizers
Bxx	$BO2_{a,s}$ and $BO2_{a,w}$	BNO3 _{a,s} and BNO3 _{a,w}	$BSO4_{a,s} \mbox{ and } BSO4_{a,w}$	BNH4 _{a,s} and BNH4 _{a,w}
Вуу	$BO2_{i,s} \text{ and } BO2_{i,w}$	$BNO3_{i,s} \mbox{ and } BNO3_{i,w}$	$BSO4_{a,s} \text{ and } BSO4_{i,w}$	BNH4 _{a,s} and BNH4 _{i,w}
Kxx	$1 - kmax1 \\ \times \left(\frac{DOC}{ksodoc1 + DOC}\right) \\ \times \left(\frac{O2}{ksox1 + O2}\right) \\ /O2min$	$\times \left(\frac{kindox + 02}{kindox + 02} \right)$	$1 - kmax3$ $\times \left(\frac{DOC}{kssdoc + DOC}\right)$ $\times \left(\frac{SO4}{ksso4 + SO4}\right)$ $\times \left(\frac{kindox}{kindox + O2}\right)$ $\times \left(\frac{kinno3}{kinno3 + NO3}\right)$ /SO4min	$1 - kmax4 \\ \times \left(\frac{NH4}{ksamm + NH4}\right) \\ \times \left(\frac{O2}{ksox + O2}\right) \\ /NH4min$

Table A1 Expressions controlling respiration, growth, dormancy, and reactivation of microbial species.

2. Reactivation: In analogy to the deactivation rates, reactivation rates are expressed as:

725
$$r = kreac \times Byy \times \frac{1}{\frac{Kxx}{e^{\frac{Kxx}{st}}+1}}$$
 (A18)

with the term Kxx depending on the bacterial species as described in Table A1.

3. Mortality: Mortality rates follow a first-order dependency on biomass concentration:

 $r = km \times fdorm \times Bxx \tag{A19}$

For active bacteria fdorm = 1, for inactive bacteria fdorm = 0.1. Dead bacterial biomass is added to the POM pool.

A.3.5 Miscellaneous processes:

1. Hydrolysis of POC is described by first order rate kinetics:

 $r = kpd \times POC \tag{A20}$

735 2. Background autotrophic microbial growth dependent on the presence of ammonium:

$$r = NH4 limit \times kmax5 \times \left(\frac{NH4}{ksamm + NH4}\right)$$
(A21)





A.4. Parameters

A.4.1 Biogeochemical reaction network parameters

S. No.	Description	Notation	Value	Units	Source
1	Rate constant for aerobic reduction of DOC	kmax1	1	d-1	calibrated
2	Minimum biomass normalized rate value for aerobic respiration to be favourable	o2min	0.06	d ⁻¹	calibrated
3	Yield coefficient for growth of aerobic degraders of DOC	Yo	0.25	-	calibrated, based on Thullner et al., 2005
4	Half-velocity DOC concentration	ksodoc	1,000	μMC	calibrated, based on concentrations observed in the field
5	Half velocity oxygen concentration	ksox	2-	μΜ	Thullner et al. (2005), Wang and van Cappellen (1996)
6	Rate constant for nitrate reduction	kmax2	0.9	d ⁻¹	calibrated, based on Schäfer et al.(1998b)
7	Minimum biomass normalized rate value for respiration to be favourable	no3min	0.1	d ⁻¹	calibrated
8	Yield coefficient for growth of nitrate reducers	Yn	0.17	-	calibrated, based on Clément et al. (1997) and Thullner et al. (2005)
9	Half-velocity DOC concentration	ksndoc	1,000	μMC	calibrated, based on concentrations observed in the field
10	Half velocity nitrate concentration	ksno3	100	μΜ	calibrated, based on Clément et al. (1997) and André et al. (2011)





S. No.	Description	Notation	Value	Units	Source
11	Inhibition constant for presence of oxygen	kindox	1	μΜ	calibrated, based on detection limits of sensors defining anaerobic conditions
12	Rate constant for sulphate reduction	kmax3	0.03	d ⁻¹	calibrated
13	Minimum biomass normalized rate value for respiration to be favourable	so4min	0.0039	d ⁻¹	calibrated
14	Yield coefficient for growth of sulphate reducers	Ys	0.02	-	calibrated, based on Thullner et al. (2005)
15	Half-velocity DOC concentration	kssdoc	1,000	μMC	calibrated, based on concentrations observed in the field
16	Half velocity sulphate concentration	ksso4	1,000	μΜ	calibrated, based on Pallud and Van Cappellen (2006), Thullner et al. (2005) and Boudreau and Westrich (1984)
17	Inhibition constant for presence of oxygen	kindox	1	μΜ	calibrated, based on detection limits of sensors defining anaerobic conditions
18	Inhibition constant for presence of nitrate	kinno3	50	μΜ	calibrated
19	Rate constant for ammonia oxidation	kmax4	0.1	d-1	calibrated
20	Minimum biomass normalized rate value for respiration to be favourable	ammin	0.004	d ⁻¹	calibrated
21	Yield coefficient for growth of ammonia oxidizers	Ya	0.0038		calibrated





S. No.	Description	Notation	Value	Units	Source
22	Half-velocity Ammonia concentration	ksamm	20	μΜ	calibrated based on conditions observed in the field
23	Half velocity oxygen concentration	ksox	20	μΜ	De Brabandere et al. (2014), Kalvelage et al. (2013), Seitzinger et al. (2006)
24	Maximum/Carrying capacity at a node	Bfmax	500	μMC	calibrated, based on Fukuda et al. (1998), Vrede et al. (2002) and Grösbacher et al. (2018).
25	Mobilisation rate constant due to exceedance of carrying capacity	kdet	1	μM C d ⁻¹	calibrated, based on Clément et al. (1997)
26	Sigmoidal function slope parameter	st	0.1	-	Stolpovsky et al. (2011)
27	Minimum concentration of Ammonium for growth to remain favourable	amming	10	μΜ	calibrated based on review by Jin et al. (2013)
28	Immobilisation rate constant	katt	0.3	μM C d ⁻¹	calibrated, based on kdet
29	Deactivation/dormancy rate constant	kdeac	1	d-1	calibrated, based on Stolpovsky et al. (2016)
30	Reactivation rate constant	kreac	0.3	d-1	calibrated, based on Stolpovsky et al (2016).
31	Mortality rate constant	km	0.01	d-1	calibrated, based on Clément et al. (1997)
32	Hydrolysis constant Carbon Nitrogen ratio for	kpd	0.03	d-1	calibrated
33	hydrolysis of particulate organic matter	fcn	10:1	-	calibrated, based on Wang and van Cappellen (1996)
34	Desorption constant	kl	0.00544	-	Rittmann and McCarty (2001)
35	Rate constant for background activity	kmax5	0.00038	d-1	calibrated

Table A2 Parameters used for the biogeochemical reaction network





740 A.4.2 Transport boundary conditions

Property (units)	Value
Porosity (-)	0.2
Density (matrix, kg m ⁻³)	1,500
Density (groundwater, kg m ⁻³)	1,000
Boundary conditions for chemic	cal and microbial species at the inlet of the domain
POM (µM C)	5
DOC (µM C)	800
DO (µM)	250
Nitrate (µM)	250
Ammonium (µM)	60
Sulphate (µM)	1,500
Bx,w (µM C)	2

Table A3 Flow and transport parameterization and boundary conditions for all domains in all three flow regimes. The boundary condition for the reactive species was a Dirichlet boundary condition (fixed concentration) at the inlet of the domain.

Code Availability

- 745 The source code of OGS5 is available in an online repository (Khurana et al., 2021). The input files for all simulated scenarios are available on the same repository. In addition, we also provide the Maple worksheet and resulting BRNS dynamically linked library that is required to run the simulations in OGS#BRNS at this link. We also provide the Python scripts used for processing the raw simulation results and for generating graphics in this publication at this link. The processed datasets are also available in this 750 repository.

Data Availability

We provide the raw simulation results in an online repository (Khurana et al., 2020) along with processed data files.

Author Contribution

755 Swamini Khurana conceptualized the reaction network, defined the scenarios to be simulated, executed the simulations, analysed the results and drafted the manuscript. Anke Hildebrandt, Falk Heße and Martin





Thullner provided guidance and technical support. Martin Thullner defined and supervised the study. All co-authors contributed to the interpretation of the results and editing the manuscript.

Competing interests

760 The authors declare that they have no conflict of interest.

Acknowledgements

This study is part of the Collaborative Research Centre AquaDiva of the Friedrich Schiller University Jena, funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – SFB 1076 – Project Number 218627073. The authors would like to thank Thomas Kalbacher for his valuable support

765 in setting up the scenarios in OpenGeoSys, and Tino Rödiger for providing useful insight into the recharge dynamics at and geology of the subject site.

References

770

775

Aguilera, D. R., Jourabchi, P., Spiteri, C., and Regnier, P.: A knowledge-based reactive transport approach for the simulation of biogeochemical dynamics in Earth systems, Geochemistry, Geophysics, Geosystems, 6, n/a-n/a, 10.1029/2004gc000899, 2005.

Alewell, C., Paul, S., Lischeid, G., Küsel, K., and Gehre, M.: Characterizing the redox status in three different forested wetlands with geochemical data, Environmental Science and Technology, 40, 7609-7615, 10.1021/es061018y, 2006.

Alfreider, A., Krossbacher, M., and Psenner, R.: Groundwater samples do not reflect bacterial densities and activity in subsurface systems, Water Research, 31, 832-840, 1997.

- Arora, B., Spycher, N. F., Steefel, C. I., Molins, S., Bill, M., Conrad, M. E., Dong, W., Faybishenko, B., Tokunaga, T. K., Wan, J., Williams, K. H., and Yabusaki, S. B.: Influence of hydrological, biogeochemical and temperature transients on subsurface carbon fluxes in a flood plain environment, Biogeochemistry, 127, 367-396, 10.1007/s10533-016-0186-8, 2016.
- Ballarini, E., Beyer, C., Bauer, R. D., Griebler, C., and Bauer, S.: Model based evaluation of a contaminant plume development under aerobic and anaerobic conditions in 2D bench-scale tank experiments, Biodegradation, 25, 351-371, 10.1007/s10532-013-9665-y, 2014.
 Benk, S. A., Yan, L., Lehmann, R., Roth, V.-N., Schwab, V. F., Totsche, K. U., Küsel, K., and Gleixner, G.: Fueling Diversity in the Subsurface: Composition and Age of Dissolved Organic Matter in the Critical
- 785 Zone, Frontiers in Earth Science, 7, 10.3389/feart.2019.00296, 2019.





Centler, F., Shao, H., De Biase, C., Park, C.-H., Regnier, P., Kolditz, O., and Thullner, M.: GeoSysBRNS— A flexible multidimensional reactive transport model for simulating biogeochemical subsurface processes, Computers & Geosciences, 36, 397-405, 10.1016/j.cageo.2009.06.009, 2010.

Cole, J. J., Prairie, Y. T., Caraco, N. F., McDowell, W. H., Tranvik, L. J., Striegl, R. G., Duarte, C. M.,

790 Kortelainen, P., Downing, J. A., Middelburg, J. J., and Melack, J.: Plumbing the Global Carbon Cycle: Integrating Inland Waters into the Terrestrial Carbon Budget, Ecosystems, 10, 172-185, 10.1007/s10021-006-9013-8, 2007.

De Brabandere, L., Canfield, D. E., Dalsgaard, T., Friederich, G. E., Revsbech, N. P., Ulloa, O., and Thamdrup, B.: Vertical partitioning of nitrogen-loss processes across the oxic-anoxic interface of an oceanic oxygen minimum zone, Environ Microbiol, 16, 3041-3054, 10.1111/1462-2920.12255, 2014.

Nitrogen in a Riparian Corridor, Water Resources Research, 54, 205-222, 10.1002/2017wr022346, 2018.

- oceanic oxygen minimum zone, Environ Microbiol, 16, 3041-3054, 10.1111/1462-2920.12255, 2014.
 Ding, D.: Transport of bacteria in aquifer sediment: experiments and modeling, Hydrogeology Journal, 18, 669-679, 10.1007/s10040-009-0559-3, 2009.
 Dwivedi, D., Arora, B., Steefel, C. I., Dafflon, B., and Versteeg, R.: Hot Spots and Hot Moments of
- Eckert, D., Kürzinger, P., Bauer, R., Griebler, C., and Cirpka, O. A.: Fringe-controlled biodegradation under dynamic conditions: Quasi 2-D flow-through experiments and reactive-transport modeling, Journal of Contaminant Hydrology, 172, 100-111, https://doi.org/10.1016/j.jconhyd.2014.11.003, 2015.
 Fukuda, R., Ogawa, H., Nagata, T., and Koike, I.: Direct determination of carbon and nitrogen contents of natural bacterial assemblages in marine environments, Applied and Environmental Microbiology, 64, 3352-
- 3358, 10.1128/aem.64.9.3352-3358.1998, 1998.
 Gharasoo, M., Centler, F., Regnier, P., Harms, H., and Thullner, M.: A reactive transport modeling approach to simulate biogeochemical processes in pore structures with pore-scale heterogeneities, Environmental Modelling & Software, 30, 102-114, 10.1016/j.envsoft.2011.10.010, 2012.
 Giardino, J. R., and Houser, C.: A Summary and Future Direction of the Principles and Dynamics of the
- Critical Zone. In: Developments in Earth Surface Processes, 2015.
 Griebler, C., Mindl, B., Slezak, D., and Geiger-Kaiser, M.: Distribution patterns of attached and suspended bacteria in pristine and contaminated shallow aquifers studied with an in situ sediment exposure microcosm, Aquatic Microbial Ecology, 28, 117-129, 2002.
 Griebler, C., and Lueders, T.: Microbial biodiversity in groundwater ecosystems, Freshwater Biology, 54,
- 649-677, 10.1111/j.1365-2427.2008.02013.x, 2009.
 Grösbacher, M., Eckert, D., Cirpka, O. A., and Griebler, C.: Contaminant concentration versus flow velocity: drivers of biodegradation and microbial growth in groundwater model systems, Biodegradation, 29, 211-232, 10.1007/s10532-018-9824-2, 2018.





Harden, J. W., O'Neill, K. P., Trumbore, S. E., Veldhuis, H., and Stocks, B. J.: Moss and soil contributions

to the annual net carbon flux of a maturing boreal forest, Journal of Geophysical Research Atmospheres, 102, 28805-28816, 1997.

Heath, R. C.: Basic groundwater-hydrology, U.S. Geological Survey, U.S. Geological Survey Water-Supply Paper, 81, 1983.

Heße, F., Harms, H., Attinger, S., and Thullner, M.: Linear exchange model for the description of mass

transfer limited bioavailability at the pore scale, Environmental Science & Technology, 44, 2064-2071, 2010.

Heße, F., Prykhodko, V., Schlüter, S., and Attinger, S.: Generating random fields with a truncated powerlaw variogram: A comparison of several numerical methods, Environmental Modelling & Software, 55, 32-48, 10.1016/j.envsoft.2014.01.013, 2014.

830 Hofmann, R., and Griebler, C.: DOM and bacterial growth efficiency in oligotrophic groundwater: absence of priming and co-limitation by organic carbon and phosphorus, Aquatic Microbial Ecology, 81, 55-71, 10.3354/ame01862, 2018.

Holm, P. E., Nielsen, P. H., Albrechtsen, H. J., and Christensen, T. H.: Importance of unattached bacteria and bacteria attached to sediment in determining potentials for degradation of xenobiotic organic

contaminants in an aerobic aquifer, Applied and Environmental Microbiology, 58, 3020-3026, 10.1128/aem.58.9.3020-3026.1992, 1992.
Holt, M. S.: Sources of chemical contaminants and routes into the freshwater environment, Food and

Chemical Toxicology, 38, S21-S27, https://doi.org/10.1016/S0278-6915(99)00136-2, 2000.

Hunter, K. S., Wang, Y., and Cappellen, P. V.: Kinetic modeling of microbially-driven redox chemistry of

subsurface environments: coupling transport, microbial metabolism and geochemistry, Journal of Hydrology, 209, 53-80, 1998.
 ISO, I. O. f. S.: ISO: 17289:2014-Water quality - Determination of dissolved oxygen - Optical sensor method. 2014.

Jing, M., Heße, F., Wang, W., Fischer, T., Walther, M., Zink, M., Zech, A., Kumar, R., Samaniego, L.,

Kolditz, O., and Attinger, S.: Improved representation of groundwater at a regional scale – coupling of mesocale Hydrologic Model (mHM) with OpeneGeoSys (OGS), Geoscientific Model Development Discussions, 1-28, 10.5194/gmd-2017-231, 2017.
 Jung, H., and Meile, C.: Upscaling of microbially driven first-order reactions in heterogeneous porous

media, J Contam Hydrol, 224, 103483, 10.1016/j.jconhyd.2019.04.006, 2019.

850 Kalvelage, T., Lavik, G., Lam, P., Contreras, S., Arteaga, L., Löscher, C. R., Oschlies, A., Paulmier, A., Stramma, L., and Kuypers, M. M. M.: Nitrogen cycling driven by organic matter export in the South Pacific oxygen minimum zone, Nature Geoscience, 6, 228-234, 10.1038/ngeo1739, 2013.



860



Khurana, S., Heße, F., Hildebrandt, A., and Thullner, M.: Simulation Results: Influence of spatial heterogeneity on microibal redox dynamics in the subsurface. Zenodo, 2020.

855 Khurana, S., Heße, F., Hildebrandt, A., and Thullner, M.: Spatial heterogeneity impact on microbial redox dynamics (Version v1.0.0). Zenodo, 2021.

Kim, K. H., Yun, S. T., Choi, B. Y., Chae, G. T., Joo, Y., Kim, K., and Kim, H. S.: Hydrochemical and multivariate statistical interpretations of spatial controls of nitrate concentrations in a shallow alluvial aquifer around oxbow lakes (Osong area, central Korea), J Contam Hydrol, 107, 114-127, 10.1016/j.jconhyd.2009.04.007, 2009.

- Kim, K. H., Michael, H. A., Field, E. K., and Ullman, W. J.: Hydrologic Shifts Create Complex Transient Distributions of Particulate Organic Carbon and Biogeochemical Responses in Beach Aquifers, Journal of Geophysical Research: Biogeosciences, 124, 3024-3038, 10.1029/2019jg005114, 2019.
 King, E. L., Tuncay, K., Ortoleva, P., and Meile, C.: Modeling biogeochemical dynamics in porous media:
- 865 Practical considerations of pore scale variability, reaction networks, and microbial population dynamics in a sandy aquifer, J Contam Hydrol, 112, 130-140, 10.1016/j.jconhyd.2009.12.002, 2010. Kohlhepp, B., Lehmann, R., Seeber, P., Küsel, K., Trumbore, S. E., and Totsche, K. U.: Aquifer configuration and geostructural links control the groundwater quality in thin-bedded carbonate–siliciclastic alternations of the Hainich CZE, central Germany, Hydrology and Earth System Sciences, 21, 6091-6116,
- 10.5194/hess-21-6091-2017, 2017.
 Kolditz, O., Bauer, S., Bilke, L., Böttcher, N., Delfs, J. O., Fischer, T., Görke, U. J., Kalbacher, T., Kosakowski, G., McDermott, C. I., Park, C. H., Radu, F., Rink, K., Shao, H., Shao, H. B., Sun, F., Sun, Y. Y., Singh, A. K., Taron, J., Walther, M., Wang, W., Watanabe, N., Wu, Y., Xie, M., Xu, W., and Zehner, B.: OpenGeoSys: an open-source initiative for numerical simulation of thermo-hydro-mechanical/chemical
- 875 (THM/C) processes in porous media, Environmental Earth Sciences, 67, 589-599, 10.1007/s12665-012-1546-x, 2012.

Küsel, K., Totsche, K. U., Trumbore, S. E., Lehmann, R., Steinhäuser, C., and Herrmann, M.: How Deep Can Surface Signals Be Traced in the Critical Zone? Merging Biodiversity with Biogeochemistry Research in a Central German Muschelkalk Landscape, Frontiers in Earth Science, 4, 10.3389/feart.2016.00032,

880 2016.

885

Lehmann, K., Lehmann, R., and Totsche, K. U.: Event-driven dynamics of the total mobile inventory in undisturbed soil account for significant fluxes of particulate organic carbon, Science of the Total Environment, 756, 10.1016/j.scitotenv.2020.143774, 2021.

Liao, Z., and Cirpka, O. A.: Shape-free inference of hyporheic traveltime distributions from synthetic conservative and "smart" tracer tests in streams, Water Resources Research, 47, 10.1029/2010wr009927,

2011.





Liu, Y., Lawrence, C. R., Winnick, M. J., Hsu, H. T., Maher, K., and Druhan, J. L.: Modeling Transient Soil Moisture Limitations on Microbial Carbon Respiration, Journal of Geophysical Research: Biogeosciences, 124, 2222-2247, 10.1029/2018jg004628, 2019.

890 Lohmann, P., Benk, S., Gleixner, G., Potthast, K., Michalzik, B., Jehmlich, N., and Bergen, M. V.: Seasonal Patterns of Dominant Microbes Involved in Central Nutrient Cycles in the Subsurface, Microorganisms, 8, 10.3390/microorganisms8111694, 2020.

Manzoni, S., and Porporato, A.: Soil carbon and nitrogen mineralization: Theory and models across scales, Soil Biology and Biochemistry, 41, 1355-1379, 10.1016/j.soilbio.2009.02.031, 2009.

McMahon, S., and Parnell, J.: Weighing the deep continental biosphere, FEMS Microbiol Ecol, 87, 113-120, 10.1111/1574-6941.12196, 2014.

Meile, C., and Tuncay, K.: Scale dependence of reaction rates in porous media, Advances in Water Resources, 29, 62-71, 10.1016/j.advwatres.2005.05.007, 2006.

Molins, S., Trebotich, D., Yang, L., Ajo-Franklin, J. B., Ligocki, T. J., Shen, C., and Steefel, C. I.: Pore-

- scale controls on calcite dissolution rates from flow-through laboratory and numerical experiments, Environ Sci Technol, 48, 7453-7460, 10.1021/es5013438, 2014.
 Müller, S., and Schüler, L.: GeoStat-Framework/GSTools: Bouncy Blue (Version v1.0.1). Zenodo, http://doi.org/10.5281/zenodo.2543658, 2019.
 Müller, S.: GeoStat-Framework/ogs5py: v1.1.1 (Version v1.1.1). Zenodo, 2020.
- Murphy, E. M., Ginn, T. R., Chilakapati, A., Resch, C. T., Phillips, J. L., Wietsma, T. W., and Spadoni, C. M.: The influence of physical heterogeneity on microbial degradation and distribution in porous media, Water Resources Research, 33, 1087-1103, 10.1029/96wr03851, 1997.
 Opitz, S., Küsel, K., Spott, O., Totsche, K. U., and Herrmann, M.: Oxygen availability and distance to surface environments determine community composition and abundance of ammonia-oxidizing
- prokaroytes in two superimposed pristine limestone aquifers in the Hainich region, Germany, FEMS Microbiology Ecology, 90, 39-53, 10.1111/1574-6941.12370, 2014.
 Painter, S. L.: Multiscale Framework for Modeling Multicomponent Reactive Transport in Stream Corridors, Water Resources Research, 54, 7216-7230, 10.1029/2018wr022831, 2018.
 Powell, R. M., and Puls, R. W.: Passive sampling of groundwater monitoring wells without purging:
- 915 multilevel well chemistry and tracer disappearance, Journal of Contaminant Hydrology, 12, 51-77, 10.1016/0169-7722(93)90015-K, 1993.
 Prommer, H., Barry, D. A., and Davis, G. B.: A one-dimensional reactive multi-component transport model for biodegradation of petroleum hydrocarbons in groundwater, Environmental Modelling & Software, 14, 213-223, 1999.





- Regnier, P., O'Kane, J. P., Steefel, C. I., and vanderborght, J. P.: Modeling complex multi-component reactive-transport systems: towards a simulation environment based on the concept of a Knowledge Base, Applied Mathematical Modelling, 26, 913-927, 2002.
 Sanz-Prat, A., Lu, C., Finkel, M., and Cirpka, O. A.: On the validity of travel-time based nonlinear
- 10.1016/j.jconhyd.2015.02.003, 2015.
 Sanz-Prat, A., Lu, C., Finkel, M., and Cirpka, O. A.: Using travel times to simulate multi-dimensional bioreactive transport in time-periodic flows, J Contam Hydrol, 187, 1-17, 10.1016/j.jconhyd.2016.01.005, 2016.

Schäfer, D., Schäfer, W., and Kinzelbach, W.: Simulation of reactive processes related to biodegradation

bioreactive transport models in steady-state flow, J Contam Hydrol, 175-176, 26-43,

930 in aquifers 2. Model application to a column study on organic carbon degradation, Journal of Contaminant Hydrology, 31, 187-209, 1998a.

Schäfer, D., Schäfer, W., and Kinzelbach, W.: Simulation of reactive processes related to biodegradation in aquifers. 1. Structure of the three-dimensional reactive transport model, Journal of Contaminant Hydrology, 31, 167-186, 10.1016/S0169-7722(97)00060-0, 1998b.

935 Schlesinger, W. H., and Andrews, J. A.: Soil respiration and the global carbon cycle, Biogeochemistry, 48, 7-20, 2000.

Schwab, V. F., Herrmann, M., Roth, V.-N., Gleixner, G., Lehmann, R., Pohnert, G., Trumbore, S., Küsel, K., and Totsche, K. U.: Functional diversity of microbial communities in pristine aquifers inferred by PLFA- and sequencing-based approaches, Biogeosciences, 14, 2697-2714, 10.5194/bg-14-2697-2017,

2017.
Seitzinger, S., Harrison, J. A., J.K. Böhlke, Bouwman, A. F., Lowrance, R., Peterson, B., Tobias, C., and Drecht, G. V.: Denitrification across landscapes and waterscapes: A Synthesis, Ecological Applications, 16, 2064-2090, 2006.

Stolpovsky, K., Martinez-Lavanchy, P., Heipieper, H. J., Van Cappellen, P., and Thullner, M.:
Incorporating dormancy in dynamic microbial community models, Ecological Modelling, 222, 3092-3102, 10.1016/j.ecolmodel.2011.07.006, 2011.
Thullner, M., Van Cappellen, P., and Regnier, P.: Modeling the impact of microbial activity on redox dynamics in porous media, Geochimica Et Cosmochimica Acta, 69, 5005-5019, 10.1016/j.gca.2005.04.026, 2005.

950 Thullner, M., Regnier, P., and Van Cappellen, P.: Modeling Microbially Induced Carbon Degradation in Redox-Stratified Subsurface Environments: Concepts and Open Questions, Geomicrobiology Journal, 24, 139-155, 10.1080/01490450701459275, 2007.





Thullner, M., and Regnier, P.: Microbial Controls on the Biogeochemical Dynamics in the Subsurface, Reviews in Mineralogy and Geochemistry, 85, 265-302, 10.2138/rmg.2019.85.9, 2019.

- Tufenkji, N.: Modeling microbial transport in porous media: Traditional approaches and recent developments, Advances in Water Resources, 30, 1455-1469, 10.1016/j.advwatres.2006.05.014, 2007. van Leeuwen, F. X. R.: Safe Drinking Water: the Toxicologist's Approach, Food and Chemical Toxicology, 38, S51-S58, https://doi.org/10.1016/S0278-6915(99)00140-4, 2000. van Rossum, G., and Drake, F. L., Jr.: The Python Language Reference Manual (version 3.2), edited by:
- Drake, F. L., Jr., Network Theory Ltd, 120 pp., 2006.
 Vogel, L. E., Pot, V., Makowski, D., Garnier, P., and Baveye, P. C.: To what extent do uncertainty and sensitivity analyses help unravel the influence of microscale physical and biological drivers in soil carbon dynamics models?, Ecological Modelling, 383, 10-22, 10.1016/j.ecolmodel.2018.05.007, 2018.
 Vrede, K., Heldal, M., Norland, S., and Bratbak, G.: Elemental composition (C, N, P) and cell volume of
- 965 exponentially growing and nutrient-limited bacterioplankton, Applied and Environmental Microbiology, 68, 2965-2971, 10.1128/AEM.68.6.2965-2971.2002, 2002.
 Waldron, P. J., Wu, L., Van Nostrand, J. D., Schadt, C. W., He, Z., Watson, D. B., Jardine, P. M., Palumbo, A. V., Hazen, T. C., and Zhou, J.: Functional gene array-based analysis of microbial community structure in groundwaters with a gradient of contaminant levels, Environmental Science and Technology, 43, 3529-
- 970 3534, 10.1021/es803423p, 2009.
 Wirtz, K. W.: Control of biogeochemical cycling by mobility and metabolic strategies of microbes in the sediments: an integrated model study, FEMS Microbiology Ecology, 46, 295-306, 10.1016/s0168-6496(03)00196-x, 2003.

Yabusaki, S. B., Wilkins, M. J., Fang, Y., Williams, K. H., Arora, B., Bargar, J., Beller, H. R., Bouskill, N.

- J., Brodie, E. L., Christensen, J. N., Conrad, M. E., Danczak, R. E., King, E., Soltanian, M., R., Spycher, N. F., Steefel, C. I., Tokunaga, T. K., Versteeg, R., Waichler, S. T., and Wainwright, H. M.: Water Table Dynamics and Biogeochemical Cycling in a Shallow, Variably-Saturated Floodplain, Environmental Science & Technology, 51, 3307-3317, 10.1021/acs.est.6b04873, 2017a.
 - Yabusaki, S. B., Wilkins, M. J., Fang, Y., Williams, K. H., Arora, B., Bargar, J., Beller, H. R., Bouskill, N.
- 980 J., Brodie, E. L., Christensen, J. N., Conrad, M. E., Danczak, R. E., King, E., Soltanian, M. R., Spycher, N. F., Steefel, C. I., Tokunaga, T. K., Versteeg, R., Waichler, S. R., and Wainwright, H. M.: Water Table Dynamics and Biogeochemical Cycling in a Shallow, Variably-Saturated Floodplain, Environ Sci Technol, 51, 3307-3317, 10.1021/acs.est.6b04873, 2017b.